Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:
The following light-duty engine package(s) produced by the manufacturer are certified as described below for use in light-duty specially constructed vehicle (SPCNS). Production engines and emission control systems shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFUL LIFE (miles)		FUEL TYPE
				EXH / ORVR	EVAP	
2013	DGMXV06.2ER1	Passenger Car	"LEV II" Low Emission Vehicle (LEV II LEV)	120K	150K	Gasoline (Tier 2 Unleaded)

No.	ECS & SPECIAL FEATURES	EVAPORATIVE FAMILY (EVAF)	DISPLACEMENT (L)
1	2TWC(2), 2HO2S(2), SFI, OBD(F)	DGMXR0133ER1	6.2
*	*	*	

Maximum Allowable Curb Weight of Completed Vehicle (lbs)	Highest Allowable N/V Ratio of Completed Vehicle	Maximum Allowable Frontal Area of Completed Vehicle (ft2)	Engine Package Model
4200	26.5	*	E-ROD SCV

See the Attachment for Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:
The exhaust and evaporative emission standards, and the certification emission levels for the listed engine packages are as listed on the Attachment. Compliance with the 50^0 Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing.

BE IT FURTHER RESOLVED:
For the listed engine packages, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 2212(g), 2212(h) and the incorporated Section 5(b) [package requirements] of the California Certification Procedures for Light-Duty Engine Packages for Use in Light-Duty Specially Constructed Vehicles for 2012 and Subsequent Model Years (Certification Procedures), 2213 [emission control labels], 2214 [defects warranty], and 2215 [performance warranty].

BE IT FURTHER RESOLVED:
The manufacturer certifying engine packages under this Executive Order shall report to ARB the total number and serial numbers of the certified engine packages produced for the model year by June 30 of the year following the model year of the certified engine packages as required in Section 6 of the Certification Procedures.

Light-duty engine packages certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-E001 dated October 19, 2012.

Executed at El Monte, California on this 14th day of March 2013.

Annette Hebert, Chief
Mobile Source Operations Division

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF=* CH4 RAF = *		NMOG or NMHC STD [g/mi]	CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]	
CERT	STD	NMOG CERT [g/mi]	NMHC CERT [g/mi]		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
@ 50K		*	*	*	*	*	*	*	*	*	*	*	*	*
@ UL		0.057	*	0.090	1.6	4.2	0.02	0.07	*	18.	*	0.01	0.03	0.09
@ 50°F & 4K		*	*	*	*	*	*	*	*	*	*	*	*	*

CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure

CO [g/mi] @ 20°F & 50K			NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	9.8	SFTP @ 4000 miles	*	*	*	*	0.10	0.14	0.7	8.0	0.08	0.20	1.9	2.7
STD	10.0	SFTP @ * miles	*	*	*	*	*	*	*	*	*	*	*	*

Evaporative Family	3-Days Diurnal + Hot Soak (grams/test) @ UL		2-Days Diurnal + Hot Soak (grams/test) @ UL		Running Loss (grams/mile) @ UL		On-Board Refueling Vapor Recovery (grams/gallon) @ UL	
	CERT	STD	CERT	STD	CERT	STD	CERT	STD
DGMXR0133ER1	0.22	0.50	0.18	0.65	0.000	0.05	0.01	0.20
*	*	*	*	*	*	*	*	*
*	*	*	*	*	*	*	*	*
*	*	*	*	*	*	*	*	*

* =not applicable; **UL**=useful life; **PC**=passenger car; **LDT**=light-duty truck; **LDT1**=LDT≤6000#GVWR,0-3750#LVW; **LDT2**=LDT≤6000#GVWR,3751-5750#LVW; **LDT3**=LDT 6001-8500#GVWR,3751-5750#ALVW; **LDT4**=LDT 6001-8500#GVWR,5751-8500#ALVW; **MDV**=medium-duty vehicle; **MDV4**=MDV 8501-10000#GVWR; **MDV5**=MDV 10001-14000#GVWR; **ECS**= emission control system; **STD**= standard; **CERT**= certification; **LVW**=loaded vehicle weight; **ALVW**=adjusted LVW; **LEV**=low emission vehicle; **ULEV**=ultra LEV; **SULEV**=super ULEV; **TWC/OC**=3-way/oxidizing catalyst; **ADSTWC**=adsorbing TWC; **WU**=warm-up catalyst; **NAC**=NOx adsorption catalyst; **SCR-U/SCR-N**= selective catalytic reduction-urea/ammonia; **NH3OC**=ammonia oxidation catalyst; **CTOX/PTOX**= continuous/periodic trap oxidizer; **HO2S/O2S**=heated/oxygen sensor; **AFS**=(heated) air-fuel ratio sensor; **NOXS**= NOx sensor; **RDQS**=reductant quality sensor; **EGR**=exhaust gas recirculation; **EGRC**=EGR cooler; **AIR/AIRE**=secondary air injection (belt driven)/(electric driven); **PAIR**=pulsed AIR; **SFI/MFI**= sequentia/ multiport fuel injection; **DFI**=direct fuel injection; **TC/SC**= turbo/super charger; **CAC**=charge air cooler; **OBD (F)/(P)(B)**=full/partial/both on-board diagnostic; **DOR**=direct ozone reducing; **HCT**=Hydrocarbon Trap; **BCAN**=bleed carbon canister; prefix **2**=parallel; **(2)** suffix=series; **CNG/LNG**= compressed/liquefied natural gas; **LPG**=liquefied petroleum gas; **E85**="85%" Ethanol ("15%"gasoline) Fuel;