EXECUTIVE ORDER A-314-0198

OB Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

## IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFUL LI	FE (miles)	FUEL TYPE Gasoline (Tier 2 Unleaded	
2014	EKMXT02.45NP	LDT: <6000# GVW, 3751-	"LEV II" Super Ultra Low Emission Vehicle (LEV II	EXH / ORVR	EVAP		
	21407102.4514	5750# LVW	SULEV)	150K 150K			
No.	ECS & S	SPECIAL FEATURES	EVAPORATIVE FA		DISPLACEMENT (L)		
1	WU-TWC,TW	/C, HO2S(2), DF1, OBD(F)	EKMXR013		2.4		
*		*	*	•			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50<sup>o</sup> Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

### BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### **BE IT FURTHER RESOLVED:**

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

#### BE IT FURTHER RESOLVED:

That the listed vehicle models are granted a partial zero-emission-vehicle (PZEV) allowance of 0.2 pursuant to 13 CCR Section 1962.1 (c)(2).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_day of August 2013.

une Erik White. Chief Mobile Source Operations Division

California Environmental Protection Agency

**O** Air Resources Board

KIA

SPORTAGE 4WD

**KIA MOTORS CORPORATION** 

EXECUTIVE ORDER A-314-0198

New Passenger Cars, Light-Duty Trucks and Medlum-Duty Vehicles Page 2 of 2

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF=* CH4 RAF = *		NMOG or	HCHO=fo	maldehyde;	PM=particul	ate matter; F	RAF=react	ivity adjust	ment facto	CO=carbon r or; 2/3 D [g/te	st]=2/3 day	diumal+	
CERT	STD	NMOG	T CERT	NMHC STD [g/mi]	hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure										
0.040	0.043	CERT [g/mi]				CO [g/mi]		x [g/mi]		CHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi	
					CERT	STD	CERT	STD	CEF	RT S	TD	CERT	STD	CERT	STE
	@ 50K	*	*	*	*	*	*	*	*		*	*	*	*	*
	@ UL	0.004	*	0.010	0.2	1.0	0.004	0.02	*		4.	*	0.01	0.01	0.03
Atta (	0 50°F & 4K	0.012	*	0.020	0.5	1.0	0.001	0.02	*		8.	*	*	•	*
CO [g/mi] @ 20°F & 50K		· *****		NMHC+NO (compo				NMHC+ [g/mi] [L			NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
				CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STE
ERT	1.5	SFTP @ 4	000 miles	*	*	*	*	0.004	0.25	2.6	10.5	0.004	0.27	0.2	3.5
STD	12.5	SFTP	@* miles	*	*	. *	*	*		*	*	*	*	*	*
Evaporative Family		3-Days Diurnal + Hot Soak (grams/test) @ UL			2-Days Diurnal + Hot Soak (grams/test) @ UL			Running Loss (grams/mile) @ UL			On-Board Refueling Vapor Recovery (grams/gallon) @ UL				
			CERT	S	D	CERT STD		CERT STD		CERT		STD			
EKMXR01375N3		N3	0.29	0.	50	0.31	0	.50	0.02 0.05		0.05	0.01		0.20	
*		*		•	*		*	*		*		*		*	
*		*			*		*	*		*	*		*		
*			*	*		*	*		* *		*	* *		*	
	lieshler III -	und il life.	DO		T-Uable	Later town less	DTALD	T-0000#C		2750411	AA/- 1 D	TO-L DT -CO	0040104	0 0754 57	E0#11/
DT3=LC 0000#G ALVW=a WU=warr oxidation AFS=Wid sensor; E sequentia liagnostic	Dicable; UL= T 6001-8500 VWR; MDV5 djusted LVW n-up catalyst; CT( le range/line: GR=exhaust GR=exhaust c; DOR=dire sed/liquefied	#GVWR,3 =MDV 100 ; LEV=low ; NAC=NO. OX/PTOX= ar/heated a gas recircu gas recircu gas recircu gas recircu	751-5750#/ 01-14000#0 emission ve x adsorptior continuous ir-fuel ratio ulation; EGF t; DFI=direc educing; HC	ALVW; LDT GVWR; EC chicle; ULE catalyst; \$ /periodic tra sensor; NC RC=EGR co t fuel inject T=Hydroca	4=LĎT 6 S= emiss V=ultra L SCR-U or ap oxidize DXS= NO boler; AIR ion; TC/S rbon Tran	001-8500# sion control EV; SULEV r SCRC/SC er; DPF = D x sensor; F X/AIRE=sec SC= turbo/s b; BCAN=b	GVWR,55 system; \$ V=super L R-N or S Diesel Part RDQS=rec condary ai super chan bleed carb	751-8500# STD= stan JLEV; TWO CRC-NH3 ticulate Fil ductant qu r injection rger; CAC on caniste	ALVW; I dard; CE C/OC=3- = selecti ter (activ ality sen (belt driv =charge er; prefix	MDV=me ERT= cert way/oxid ive cataly ve); HO2S sor; NH3 ven)/(elect air coole 2=paralle	edium-d tification lizing ca tic redu S/O2S= S = Am ctric driv r; OBD	uty vehicle; h; LVW=loa talyst; ADS ction-urea/a heated/oxyg monia sens ven); PAIR= (F)/(P)(B)=	MDV4=N ded vehic TWC=ad ammonia; gen sensc sor; PMS= =pulsed A full/partia	NDV 8501- sorbing TV NH3OC=a or; WR-HO particulate IR; SFI/MF I/both on-b	VC; ammoni 2S or matter

EKMXR01375N3

1

2.4

LDT2

HCT

Full