NISSAN MOTOR COMPANY, LTD.

EXECUTIVE ORDER A-015-0639-1

OB Air Resources Board

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY				
2014	ENSXV03.7GAB	Passenger Car	"LEV II" Ultra Low Emission	EXH / ORVR	EVAP	Gasoline	
			Vehicle (LEV II ULEV)	120K	150K		
No.	ECS & SPE	CIAL FEATURES	THE R. L. LEWIS CO. LANSING MICH.	EVAPORATIVE FAMILY (EVAF)			
1	2TWC(2), 2AFS	,2HO2S, SFI, OBD(F)	ENSXR0120	ENSXR0120MBA			
*		*	*	•			
*			•				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-015-0639 dated June 21, 2013.

Executed at El Monte, California on this ______d

30 day of October 2013. Erik White, Chief Mobile Source Operations Division

California Environmental Protection Agency

O Air Resources Board

NISSAN MOTOR COMPANY, LTD.

EXECUTIVE ORDER A-015-0639-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]		NMOG @ RAF=* CH4 RAF = *		NMOG or	CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diumal+											
CERT	RT STD NMOG		NMHC	NMHC		hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram ml=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure										
0.007	0.025	CERT	CERT	STD [g/mi]	CO [g/mi]		NOx [g/mi]			CHO [mg/		PM [g/mi]		Hwy NOx [g/m		
0.027 0.035		[g/mi]	[g/mi]	[9/m]	CERT	STD	CERT	STD	CE	RTS	TD	CERT	STD	CERT	ST	
A PARTY	@ 50K	0.014	*	0.040	. 0.4	1.7	0.02	0.05		*	8.	*	*	0.004	0.0	
	@ UL	0.014	*	0.055	0.5	2.1	0.02	0.07		*	11.	*	0.01	0.004	0.0	
98 6 C	0 50°F & 4K	0.055	+	0.080	0.5	1.7	0.03	0.05		*	16.	*	*	*	*	
CO [g/ml] @ 20°F & 50K				NMHC+NOx [g/mi] (composite)			CO [g/mi] NMHC (composite) [g/mi] [NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
		· · · · · · · · · · · · · · · · · · ·		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	ST	
ERT	1.0	SFTP @ 4	000 miles	*	*	*	*	0.03	0.14	0.5	8.0	0.02	0.20	0.4	2.7	
STD	10.0	SFTP	@* miles	*	*	*	*	*	*	*	*	*	*	*	*	
Evaporative Family 3-Days Diurnal + H (grams/test) ENSXR0120MBA 0.36 * * * *							Running Loss (grams/mile) @ UL			On-Board Refueling Vapor Recovery (grams/gallon) @ UL						
			CERT	ST	TD CERT		S	STD		CERT STD		CERT		STD		
		BA	0.36	0.	50	0.34	0.65		0.001		0.05	0.01		0.20		
			*			*		•	*		*		*		*	
			*					*	*	*		*		*		
-	*		*	*		*		*	*	*			*		*	
DT3=LE 0000#G LVW=a VU=warr xidation FS=Wid ensor; E equentia iagnostic	plicable; UL= DT 6001-8500 VWR; MDV8 djusted LVWM n-up catalyst catalyst; CT(de range/lines GR=exhauss al/ multiport fin c; DOR=dire sed/liquefied	0#GVWR,3 =MDV 100 ; LEV=low ; NAC=NO OX/PTOX= ar/heated a t gas recirc uel injection ect ozone re	0751-5750#, emission vo x adsorptio continuous ir-fuel ratio ulation; EG n; DFI=direc educing; HC	ALVW; LDT GVWR; EC ahicle; ULE n catalyst; S /periodic tra sensor; NC RC=EGR co t fuel injecti T=Hydroca	4=LDT 6 S= emiss V=ultra Ll SCR-U or ap oxidize DXS= NO boler; AIR ion; TC/S rbon Trap	001-8500# ion control EV; SULEY SCRC/SO er; DPF = E x sensor; F XAIRE=sec C= turbo/s b; BCAN=t	GVWR,5 system; S V=super L R-N or S Diesel Par RDQS=rec condary a super cha	751-8500 STD= star JLEV; TW CRC-NH: ticulate Fi ductant qu ir injection rger; CAC ion canist	#ALVW adard; C C/OC=: 3= select iter (action belt difference) c) c) c	MDV=me ERT= cer 3-way/oxic tive cataly ive); HO2 nsor; NH3 riven)/(ele e air coole x 2=parall	edium-d tification lizing ca tic redu S/O2S= S = Am ctric driv er: OBD	uty vehicle; h; LVW=loa talyst; ADS ction-urea/ heated/oxy monia sens ven); PAIR: (F)/(P)(B)=	MDV4=N ded vehic TWC=ad ammonia; gen senso sor; PMS= =pulsed A full/partia	NDV 8501- cle weight; sorbing TV NH3OC=; or; WR-HO particulate IR; SFI/MI	VC; ammor 2S or e matter FI=	
ompress	sedniquened	laturai gas		14 MOD			Start - a-		ELS IN	FORM	ATIO	N			-	
	AKE		MOD		1	EVAPO	RATIVE	EC	SE	NGINE	VE	HICLE	SPE	IAL	00	

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	VEHICLE TYPE	SPECIAL FEATURES	OBD II	
INFINITI	Q60 Convertible	ENSXR0120MBA	1	3.7	PC	*	Full	
INFINITI	Q70 AWD	ENSXR0120MBA	1	3.7	PC		Full	