California Environmental Protection Agency		EXECUTIVE ORDER A-010-1823		
O Air Resources Board	FORD MOTOR COMPANY	New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles		

Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFUL LI	FE (miles)	FUEL TYPE	
2015 FFMXD03.77BU MI	MDV: 10001-14000# GVW	"LEV II" Ultra Low Emission	EXH / ORVR	EVAP	Gasoline (Tier 2 Unleaded		
	WEV. 10001-14000# CVVV	Vehicle (LEV II ULEV)	120K 150K				
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE FAM	EVAPORATIVE FAMILY (EVAF)			
1	2TWC, 2AF	S, 2HO2S, SFI, OBD(F)	FFMXF0190	FFMXF0190NBS			
*	and the state of the second state of	*	*	*			
*		*	*	*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV, amended December 6, 2012).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT, and MDV, amended December 6, 2012 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a largevolume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volumemanufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

day of March 2014.

Executed at El Monte, California on this _

uneras nette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

Air Resources Board

FORD MOTOR COMPANY

EXECUTIVE ORDER A-010-1823

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

CERT STE		NMHC		CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; r HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 23 D [gdtst]=2/3 day diurnal+ hot-soak; RL [g/m]=running loss; ORVR [g/gallon dispensed]=on-board refueiing vapor recovery; g=gram; mg=milligram										
			NMHC STD	mi=mile; K	=1000 miles	F=degrees	Fahrenhei	it; SFTP=su	plemental	federal t	test procedu	ire	an, ng-ma	Braiti
CE		CERT	[g/mi]		[g/mi]		x [g/mi]		HO [mg/I		PM [g/mi])x [g/mi]
	[g/mi] [g/mi]	faund	CERT	STD	CERT	STD	CEF		TD	CERT	STD	CERT	STD	
@!	0K *	*	*	*	*	*	*	*		*			*	*
@	UL 0.106	*	0.167	5.3	7.3	0.3	0.4	*	2	1.	*	0.06	0.2	0.8
@ 50°F &		*			*		*			*	*	*	*	*
CO [g/mi]			NMHC+NOx [g/mi] (composite) (CO [g/mi] NMHC+ (composite) [g/mi] [L				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
@ 20°F & 50K	An and a start of the second s	a second	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
ERT *	SFTF	@* miles	*	*	*	*	*	*		*		*	*	*
STD *		@* miles	*	*	*	*	*	*	*	*	*	*	*	*
							Running Loss (grams/mile) @ UL		R	On-Board Refueling Vapor Recovery (grams/gallon) @ UL				
		CERT	S	STD CER		STD		CERT STD		STD		CERT		STD
FFMXF0190NBS		0.35	1.	00	0.33	1.25		0.000 0.05					*	
*		*		•	*	*		* *		*			*	
. *	. * *			*	*	*	*	*	* '		*	*		
* *		*		* *		*		* *		*		*		
=not applicable; DT3=LDT 6001- 0000#GVWR; M VU=adjusted WU=warm-up cat xidation catalyst AFS=Wide range tensor; EGR=ext requential/ multip iganostic DOR	8500#GVWR, DV5=MDV 10 VW; LEV=lov alyst; NAC=NG CTOX/PTOX /linear/heated aust gas recin	3751-5750#, 001-14000#/ v emission vo Dx adsorptio = continuous air-fuel ratio culation; EG on; DFI=direc reducing; HC	ALVW; LDT GVWR; EC ahicle; ULE n catalyst; \$ /periodic tra sensor; NO RC=EGR c t fuel inject T=Hydroca	F4=LDT 6 S= emissi V=ultra LI SCR-U or ap oxidize OXS= NO ooler; AIR tion; TC/S arbon Trap	001-8500# ion control EV; SULE SCRC/SO er; DPF = [x sensor; I VAIRE=se SC= turbo/ b; BCAN=t	#GVWR,5 I system; V=super U CR-N or S Diesel Par RDQS=re condary a super cha	751-8500 STD= sta JLEV; TV CRC-NH ticulate F ductant q ir injectio rger; CA coon canis	#ALVW; ndard; CI VC/OC=3 3= select ilter (activ uality sen n (belt dri C=charge ter; prefix	MDV=me ERT= cer -way/oxid ive cataly /e); HO23 sor; NH3 ven)/(ele air coole 2=paralle	edium-d tification lizing ca tic redu S/O2S= S = Am ctric dri er; OBD	luty vehicl n; LVW=lo atalyst; AC uction-urea heated/ox monia se ven); PAII 0 (F)/(P)(B	e; MDV4=1 baded vehic DSTWC=ad a/ammonia aygen sens nsor; PMS R=pulsed A)=full/partia	MDV 8501- cle weight; Isorbing TV ; NH3OC= or; WR-HO =particulate AIR; SFI/MI al/both on-t	VC; ammon 2S or e matte FI=

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	VEHICLE TYPE	SPECIAL FEATURES	OBD II
FORD	TRANSIT T350 CHASSIS CAB	FFMXF0190NBS	1	3.7	MDV5		Full
FORD	TRANSIT T350 CUTAWAY	FFMXF0190NBS	1	3.7	MDV5	•	Full