Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED:
The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION				
MODEL YEAR	TEST GROUP	VEHICLE CLASS(ES)	FUEL CATEGORY	FUEL TYPE
2015	FJLXV03.0FSP	PC	DEDICATED SINGLE FUEL VEHICLE	GASOLINE

USEFUL LIFE (miles)		VEHICLE EMISSION CATEGORY		INTERIM / INTERMEDIATE IN-USE STD	
EXH/ORVR	EVAP	FTP	SFTP	FTP	SFTP
150,000	150,000	LEV3 SULEV30	LEV3 SULEV STAND-ALONE	*	NMOG+NOx

SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS		OBD STATUS		ENGINE DISPLACEMENT (L)
1	2TWC, 2AFS, 2HO2S(2), DFI, SC, CAC	FULL	ALL MODELS	3.0
*	*	PARTIAL	*	
*	*	PARTIAL WITH FINES	*	

EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION		
EVAP / ORVR FAMILY	EVAPORATIVE STD CATEGORY	EVAP EMISSION STD VEHICLE CLASS
FJLXR0160P1Z	LEV3 OPTION 2	PC
*	*	*
*	*	*

EMISSION CREDIT INFORMATION					
ALLOWANCE FOR TEST GROUP			NMOG CREDIT FOR NON-PZEV ZERO-EVAP	NMOG CREDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS
BASELINE PZEV	AT PZEV	TZEV			
ALL MODELS	*	*	N	N	N

NMOG AND FLEET AVERAGE INFORMATION					
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+NOX FLEET STD PC+LDT (0-3750 LVW) (g/mi)	NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)
*	*	1.10	*	0.100	0.119

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:
The exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50^0 Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG+NOx Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:
For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV, amended December 6, 2012).

BE IT FURTHER RESOLVED:
The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT, and MDV, amended December 6, 2012 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the

CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

BE IT FURTHER RESOLVED:
The listed vehicle models have been certified using assigned deterioration factors for evaporative emissions on the condition that the manufacturer complete deterioration factor development and provide new evaporative emission deterioration factors by October 24, 2014. Failure to submit the deterioration factors by the specified date, or failure of the submitted test data to show compliance with the emission standards, shall be cause for the Air Resources Board to revoke this Executive Order and vehicles sold under the revoked conditional certification shall be deemed uncertified.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.
The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 26th day of June 2014.

Annette Hebert, Chief
Emissions Compliance, Automotive Regulations and Science Division

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50 °F, 20 °F)

CH4=methane; **NMOG**=non-CH4 organic gas; **HC**=hydrocarbon; **NMHC**=non-CH4 HC; **CO**=carbon monoxide; **NOx**=oxides of nitrogen; **HCHO**=formaldehyde; **PM**=particulate matter; **RAF**=reactivity adjustment factor; **2DHS/3DHS** [g HC/test]=2/3 days diurnal+hot-soak; **RL** [g HC/mi]=running loss; **ORVR** [g HC/gallon dispensed]=on-board refueling vapor recovery; **g**=gram; **mg**=milligram; **mi**=mile; **K**=1000 miles; **F**=degrees Fahrenheit; **FTP**=federal test procedure; **SFTP**=supplemental FTP

	FUEL TYPE	NMOG+NOx (g/mi)		CO (g/mi)		HCHO (mg/mi)		PM (g/mi)		HWY NMOG+NOx (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP @ 50K	*	*	*	*	*	*	*	*	*	*	*
FTP @ UL	GASOLINE-LEV3 E10	0.023	0.030	0.4	1.0	0.2	4	0.002	0.01	0.008	0.030
20°F @ 50K	GASOLINE-COLD CO LOW OCTANE	*	*	1.3	10.0	*	*	*	*	*	*
50°F @ 4K	GASOLINE-LEV3 E10	0.059	0.060	0.4	1.0	1	8	*	*	*	*

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	FUEL TYPE	US06 / UC (LA92)						SC03				COMPOSITE				
		NMOG+NOx (g/mi)		CO (g/mi)		PM (mg/mi)		NMOG+NOx (g/mi)		CO (g/mi)		NMOG+NOx (g/mi)			CO (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	BIN	CERT	STD
@ UL	GASOLINE-LEV3 E10	0.030	0.050	0.8	9.6	*	*	0.014	0.020	0.4	3.2	*	*	*	*	*

WHOLE VEHICLE EVAPORATIVE/ORVR EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY	FUEL TYPE	WHOLE VEHICLE EVAPORATIVE TESTING						RUNNING LOSS (g/mi) @ UL		ON-BOARD REFUELING VAPOR RECOVERY (g/gallon) @ UL	
		3-DAYS DIURNAL + HOT SOAK (g/test) @ UL			2-DAYS DIURNAL + HOT SOAK (g/test) @ UL						
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD	CERT	STD
FJLXR0160P1Z	GASOLINE-LEV3 E10	0.245	0.300	*	*	0.300	*	0.001	0.05	0.01	0.20

FUEL ONLY & CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY	FUEL TYPE	FUEL ONLY EVAPORATIVE TESTING				CANISTER BLEED (g/test)	
		3-DAYS DIURNAL + HOT SOAK (g/test) @ UL		2-DAYS DIURNAL + HOT SOAK (g/test) @ UL			
		CERT	STD	CERT	STD	CERT	STD
FJLXR0160P1Z	GASOLINE-LEV3 E10	*	*	*	*	0.015	0.020
*	*	*	*	*	*	*	*

* =not applicable; **#**=pounds; **UL**=useful life; **PC**=passenger car; **LDT**=light-duty truck; **LDT1**=LDT≤6000#GVWR,0-3750#LVW; **LDT2**=LDT≤6000#GVWR,3751-5750#LVW; **LDT3**=LDT 6001-8500#GVWR,3751-5750#ALVW; **LDT4**=LDT 6001-8500#GVWR,5751-8500#ALVW; **MDV**=medium-duty vehicle; **MDV4**=MDV 8501-10000#GVWR; **MDV5**=MDV 10001-14000#GVWR; **MDPV**=medium-duty passenger vehicle; **ECS**=emission control system; **CERT**=certification; **STD**=standard; **FEL**=family emission limit; **GVWR**=gross vehicle weight rating; **LVW**=loaded vehicle weight; **ALVW**=adjusted LVW; **LEV**=low emission vehicle; **ULEV**=ultra LEV; **SULEV**=super ULEV; **ZEV**=zero-emission vehicle; **PZEV**=partial ZEV; **AT PZEV**=advanced technology PZEV; **TZEV**=transitional ZEV; **TWC/OC**=3-way/oxidizing catalyst; **ADSTWC**=adsorbing TWC; **HAC**=HC adsorbing catalyst; **WU**=warm-up catalyst; **NAC**=NOx adsorption catalyst; **SCR-U or SCRC/SCR-N or SCRC-NH3**=selective catalytic reduction-urea/ammonia; **NH3OC**=ammonia oxidation catalyst; **CTOX/PTOX**= continuous/periodic trap oxidizer; **DPF**=diesel particulate filter (active); **GPF**=PM filter for spark-ignited engine; **HO2S/O2S**=heated/oxygen sensor; **WR-HO2S or AFS**=wide range/linear/heated air-fuel ratio sensor; **NOXS**=NOx sensor; **PMS**=PM sensor; **RDQS**=reductant quality sensor; **NH3S**=ammonia sensor; **EGR**=exhaust gas recirculation; **EGRC**=EGR cooler; **AIR/AIRE**=secondary air injection (belt driven)/(electric driven); **PAIR**=pulsed AIR; **SFI/MFI**=sequential/multiport fuel injection; **DFI/IFI**=direct/indirect fuel injection; **TC/SC**= turbo/super charger; **CAC**=charge air cooler; **F/P/$**=full/partial/partial with fines on-board diagnostic; **DOR**=direct ozone reducing; **HCT**=hydrocarbon trap; **BCAN**=bleed carbon canister; prefix **2**=parallel; **(2)** suffix=series; **CNG/LNG**=compressed/liquefied natural gas; **LPG**=liquefied petroleum gas; **E85**="85%" ethanol ("15%"gasoline) fuel; **E10**="10%" ethanol ("90%"gasoline) fuel; **A**=automatic transmission; **M**=manual transmission; **SA**=semi-automatic transmission; **L**=lock-up automatic transmission; **CV**=continuously variable transmission; **AM**=automated manual transmission; **OT**=other transmission

2015 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
JAGUAR	XF	PC	3.0	SA8	FJLXR0160P1Z	1	FULL	PZEV
JAGUAR	XF AWD	PC	3.0	SA8	FJLXR0160P1Z	1	FULL	PZEV
JAGUAR	F-TYPE COUPE	PC	3.0	SA8	FJLXR0160P1Z	1	FULL	PZEV
JAGUAR	F-TYPE CONVERTIBLE	PC	3.0	SA8	FJLXR0160P1Z	1	FULL	PZEV

JAGUAR	F-TYPE S COUPE	PC	3.0	SA8	FJLXR0160P1Z	1	FULL	PZEV
JAGUAR	F-TYPE S CONVERTIBLE	PC	3.0	SA8	FJLXR0160P1Z	1	FULL	PZEV