EXECUTIVE ORDER A-016-0421

OB Air Resources Board

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

# IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEAR	TEST GROUP VEHICLE TYPE		VEHICLE TYPE EXHAUST EMISSION USEFUL LI				
2015	FTKXV02.55BA	Passenger Car	"LEV II" Ultra Low Emission	EXH / ORVR	EVAP	- Gasoline (Tier 2 Unleaded	
	1100002.0300	r assenger Oar	Vehicle (LEV II ULEV)	120K 150K		Casoline (The 2 Officade	
No.	ECS & SPI	ECIAL FEATURES	EVAPORATIVE FAM		DISPLACEMENT (L)		
1	WU-TWC, TWC, WR	-HO2S, HO2S, DFI, OBD(F)	FTKXR0120		2.5		
*	and the second s	*					
+		*					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

# **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

# **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### **BE IT FURTHER RESOLVED:**

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

#### **BE IT FURTHER RESOLVED:**

Vehicles certified under this Executive Order shall not be introduced into commerce before January 2, 2014.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 27th day of December 2013.

Erik White, Chief

Mobile Source Operations Division

California Environmental Protection Agency

OB Air Resources Board

MAZDA MOTOR CORPORATION

EXECUTIVE ORDER A-016-0421

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

			@ RAF=* {AF = *	NMOG or	CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal-											
CERT			NMHC	NMHC	mi=mile;	hot-soak, RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure										
0.000	0.400	CERT	RT CERT	STD [g/mi]		[g/mi]				ICHO [mg/mi]		PM [g		Hwy N	Ox [g/mi]	
0.069	0.100	[g/mi]			CERT	STD	CERT	STD	CE	RT S	TD	CERT	STD	CERT	STE	
and the second se	@ 50K	0.010	*	0.040	0.2	1.7	0.01	0.05			8.	*	*	0.004	0.0	
	@ UL	0.013	*	0.055	0.2	2.1	0.01	0.07			1.	*	0.01	0.005	0.09	
@ 50°F & 4K 0.020		0.020	*	0.080	0.3	1.7	0.01	0.05		1	6.	*	*	*	*	
CO [g/mi] @ 20°F & 50K				NMHC+NC (compo				NMHC+NO: [g/mi] [US06				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
				CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STE	
ERT	0.5	SFTP @ 4	000 miles	*	*	*	*	0.03	0.14	0.2	8.0	0.04	0.20	0.3	2.7	
STD	10.0	SFTP	@* miles	*	*	*	*	*	*	*	*	*	*	*	*	
Evaporative Family		mily		urnal + Hot ns/test) @ U			urnal + Hot Soak s/test) @ UL		Running Loss (grams/mile) @ UL				Refueling Vapor rams/gallon) @ UL			
			CERT	ST	D	CERT	S	TD	CER	Т	STD		CERT		STD	
FTKXR0120GAK		AK	0.16	0.50		*	0	0.65 0.0				0.01			0.20	
*			*						*	*		*		*		
*			*			*	*		* *			*		*		
*			*			*		*	*		*		*		*	
=not app	plicable; UL:	useful life;	PC=passer	nger car; LI	DT=light-o	duty truck;	LDT1=LD	T_6000#	GVWR,0	-3750#L\	W; LD	T2=LDT<6	000#GVW	VR,3751-5	750#LV	
DT3=LD 0000#G ALVW=ac VU=warn xidation AFS=Wid ensor; E equentia liagnostic	T 6001-850 VVR; <b>MDV</b> djusted LVW m-up catalys catalyst; CT de range/line GR=exhaus al/ multiport f c; DOR=dire	0#GVWR,3 5=MDV 100 /; LEV=low t; NAC=NO OX/PTOX= ar/heated a t gas recirc uel injection ect ozone re	3751-5750#/ emission vo adsorptio continuous air-fuel ratio ulation; EG n; DFI=direc educing; HC	ALVW; LDT GVWR; EC ehicle; ULE n catalyst; \$ /periodic tra sensor; NC RC=EGR co t fuel inject T=Hydroca	T4=LDT 6 S= emiss V=ultra L SCR-U or ap oxidize DXS= NO pooler; AIR ion; TC/S proon Trap	ion control EV; SULE SCRC/SC er; DPF = [ X sensor; l XAIRE=se SC= turbo/ p; BCAN=l	GVWR,5 I system; S V=super L CR-N or S Diesel Par RDQS=re condary a super cha bleed carb	751-8500 STD= star JLEV; TW CRC-NH: ticulate Fi ductant qu ir injection rger; CAC bon cariist	#ALVW; ndard; C /C/OC=3 3= selec ilter (acti uality sen (belt dr C=charge er; prefix	MDV=me ERT= cer I-way/oxid tive cataly ve); HO2 isor; NH3 iven)/(ele air coole c 2=paralle	edium-d tification lizing ca tric redu S/O2S= S = Am ctric driv er; OBD	uty vehicle n; LVW=loa italyst; ADS iction-urea/ heated/oxy monia sen ven); PAIR (F)/(P)(B)	; MDV4=N aded vehic STWC=ad /ammonia /gen sens sor; PMS =pulsed A =full/partia	MDV 8501 cle weight; sorbing T ; NH3OC= or; WR-H0 =particulat MR; SFI/M al/both on-	WC; ammon D2S or te matter IFI=	
DT3=LD 0000#G LVW=ac /U=warn xidation .FS=Wid ensor; E equentia iagnostic	OT 6001-850 VVVR; <b>MDV</b> djusted LVV m-up catalys catalyst; CT de range/line GR=exhaus al/ multiport f	0#GVWR,3 5=MDV 100 /; LEV=low t; NAC=NO OX/PTOX= ar/heated a t gas recirc uel injection ect ozone re	0751-5750#, 001-14000#4 emission ver- x adsorptio continuous air-fuel ratio ulation; EGI n; DFI=direc educing; HC s; LPG=liqu	ALVW; LDT GVWR; EC ehicle; ULE n catalyst; \$ /periodic tra sensor; NC RC=EGR co t fuel inject T=Hydroca	F4=LDT 6 S= emiss V=ultra L SCR-U or ap oxidize DXS= NO coler; AIR ion; TC/S irbon Trap leum gas	ion control EV; SULE r SCRC/SC er; DPF = [ XAIRE=se SC= turbo/ p; BCAN=1 ; E85="85	#GVWR,5 I system; S V=super I CR-N or S Diesel Par RDQS=re condary a super cha bleed carb %" Ethance	751-8500 STD= star JLEV; TW CRC-NH: ticulate Fi ductant qu ir injection rger; CAC bon canist bl ("15%"c	#ALVW; hdard; C IC/OC=3 3= selec liter (acti uality sen h (belt dr C=charge er; prefix gasoline)	MDV=me ERT= cer a-way/oxic tive cataly ve); HO2: hsor; NH3 iven)/(ele air coole c 2=paralli Fuel;	edium-d tification lizing ca ttic redu S/O2S= S = Am ctric driv er; OBD el; (2) so	uty vehicle n; LVW=loa ttalyst; ADS ction-urea heated/oxy monia sen ven); PAIR (F)/(P)(B): uffix=series	; MDV4=N aded vehic STWC=ad /ammonia /gen sens sor; PMS =pulsed A =full/partia	MDV 8501 cle weight; sorbing T ; NH3OC= or; WR-H0 =particulat MR; SFI/M al/both on-	WC; ammon 02S or te matte IFI=	
DT3=LD 0000#G' LLWEac VU=warm xidation LFS=Wid ensor; E sequentia iagnostic ompress	T 6001-850 VVR; <b>MDV</b> djusted LVW m-up catalys catalyst; CT de range/line GR=exhaus al/ multiport f c; DOR=dire	0#GVWR,3 5=MDV 100 /; LEV=low t; NAC=NO OX/PTOX= ar/heated a t gas recirc uel injection ect ozone re	0751-5750#, 001-14000#4 emission ver- x adsorptio continuous air-fuel ratio ulation; EGI n; DFI=direc educing; HC s; LPG=liqu	ALVW; LDT GVWR; EC ehicle; ULE in catalyst; § /periodic tr sensor; NC RC=EGR ci t; fuel inject T=Hydroca lefied petro	F4=LDT 6 S= emiss V=ultra L SCR-U or ap oxidize DXS= NO coler; AIR ion; TC/S irbon Trap leum gas	001-8500# ion control EV; SULE r SCRC/SC er; DPF = I X sensor; VAIRE=se SC= turbo/ p; BCAN=1 ; E85="85 AR: VI	#GVWR,5 I system; S V=super I CR-N or S Diesel Par RDQS=re condary a super cha bleed carb %" Ethance	751-8500 STD= star JLEV; TW CRC-NH: ticulate Fi ductant qu ir injection rger; CAC bon canist bl ("15%"c	#ALVW; hdard; C (C/OC=3 3= selec liter (acti- uality see h (belt dr C=charge er; prefib- gasoline) ELS IN S E	MDV=me ERT= cer a-way/oxic tive cataly ve); HO2: hsor; NH3 iven)/(ele air coole c 2=paralli Fuel;	edium-d tification lizing ca tic redu S/O2S= S = Am ctric driver; OBD el; (2) so ATIO	uty vehicle n; LVW=loa ttalyst; ADS ction-urea heated/oxy monia sen ven); PAIR (F)/(P)(B): uffix=series	; MDV4=M aded vehic STWC=ad /ammonia /gen sens: sor; PMS =full/partia s; CNG/L SPE	MDV 8501 cle weight; sorbing T ; NH3OC= or; WR-H0 =particulat MR; SFI/M al/both on-	WC; ammon 02S or te matte IFI=	