California Environmental Protection Agency	FORD MOTOR	Executive Order: A-010-1899 . New Passenger Cars, Light-Duty Trucks a				
OB Air Resources Board	COMPANY	Medium-Duty Vehicles				
An Hesodices Board		Page 1 of 4				

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					٦	EST GROUP	INFOR	MATION				
MOD		TEST G	ROUP	VE	HICLE	CLASS(ES)	FUEL CATEGORY			FUEL TYPE		
201	6 GFMXT02.52ET LDT2					DT2			SINGLE FUEL	CASOLT		
	USEF	JL LIFE	miles)		EHIC	LE EMISSION	CATE	GORY	INTERIM / INT	FERMEDIA	TE IN-USE STD	
						P	SF	TP	FTP	SFTP		
120000 150000 LEV2 ULEV						ULEV		SFTP	*	*		
SP	ECIAL	FEATUR			SSION	CONTROL	100	OBD ST	TATUS	ENGINE	DISPLACEMENT (L)	
1	TWC, WR-HO2S, HO2S, EGR, SFI							FULL	*			
*				*			F	PARTIAL ALL MODELS		2.5		
*				*			PAR	RTIAL WITH	*			
				EVAPORATIV	E&RE	FUELING (E	VAP/OF	RVR) FAMILY	INFORMATION			
EV	AP / OF		ILY	EVAPORAT	TIVE S	TD CATEGO	RY	EVAP EMIS	SSION STD	SPECIA	L FEATURES	
	GFMXR	0125NBV			LEV	2		LD	T2	*		
					EM	ISSION CRE	DIT INF	ORMATION				
		ALLOW	ANCE	FOR TEST GR	OUP			G CREDIT FO	NMOG CR	EDIT FOR	OPTIONAL EXH	
BASELINE PZEV AT PZEV TZEV						TZEV	EVAP			TRUCKS		
* * *						*	N			N N		
				NN	IOG A	ND FLEET A	VERAG	E INFORMA	ΓΙΟΝ			
NMO	MOG RAF CH4 RAF FTP NMOG/NMHC H			HCHO/NMHC RATI		TIO NMOG+NOX FLEET S PC+LDT (0-3750 LVV (g/mi)						
	*	*		1.04		*			0.093		0.110	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. California Environmental Protection Agency

OB Air Resources Board

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of May 2015.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division California Environmental Protection Agency

**OB** Air Resources Board

FUEL TYPE

FORD MOTOR COMPANY

Executive Order: A-010-1899 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

## ATTACHMENT

### EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				CO (g/mi)			NOx (g/mi)				PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CEF	RT STD	
TP@50K T1		0.019	0.040	0.8	1.7	0.03	0.05	*	8	*	*	
TI	ER 2 0.026		0.055	1.0	2.1	0.06	0.07	*	11	*	0.01	
	*	*	*	*	*	*	*	*	*	ALL		
E STREET				-			NOx (	g/mi)	CO (g/mi)			
0		FUEL TYPE					CERT		CERT		STD	
50K	(	- TIER :	0.	0.02 0.07								
UL	GASOLINE - TIER 2 UNLEADED						05	0.09				
50K	GASOLINE-COLD CO LOW OCTANE						1		2.	.0	12.5	
	TI UNI GASC TI UNI 50K	50K (0) 0) UL (0)	(g/) CERT GASOLINE - TIER 2 UNLEADED GASOLINE - TIER 2 UNLEADED * * 50K GASOLINE QUL GASOLINE	GASOLINE - TIER 2 UNLEADED GASOLINE - TIER 2 UNLEADED * * * * 50K GASOLINE - TIER 2 50K GASOLINE - TIER 2 UL GASOLINE - TIER 2	(g/mi) (g/mi)   CERT STD CERT   GASOLINE - TIER 2 0.019 0.040 0.8   UNLEADED 0.026 0.055 1.0   GASOLINE - TIER 2 0.026 0.055 1.0   VNLEADED * * *   50K GASOLINE - TIER 2 UNLEAD   QUL GASOLINE - TIER 2 UNLEAD	(g/mi) (g/mi)   CERT STD CERT STD   GASOLINE - TIER 2 UNLEADED 0.019 0.040 0.8 1.7   GASOLINE - TIER 2 UNLEADED 0.026 0.055 1.0 2.1   * * * * * *   50K GASOLINE - TIER 2 UNLEADED UNLEADED 0.026 0.055 1.0 2.1   * * * * * * *	(g/mi) (g/mi) (g/mi) (g/mi)   CERT STD CERT STD CERT   GASOLINE - TIER 2 UNLEADED 0.019 0.040 0.8 1.7 0.03   GASOLINE - TIER 2 UNLEADED 0.026 0.055 1.0 2.1 0.06   VNLEADED * * * * *   GASOLINE - TIER 2 0.026 0.055 1.0 2.1 0.06   VNLEADED * * * * * *   50K GASOLINE - TIER 2 UNLEADED 0. 0. 0.   9UL GASOLINE - TIER 2 UNLEADED 0. 0.	(g/mi) (g/mi) (g/mi)   CERT STD CERT STD CERT STD   GASOLINE - TIER 2 UNLEADED 0.019 0.040 0.8 1.7 0.03 0.05   GASOLINE - TIER 2 UNLEADED 0.026 0.055 1.0 2.1 0.06 0.07   GASOLINE - TIER 2 UNLEADED 0.026 0.055 1.0 2.1 0.06 0.07   * * * * * * * *   FUEL TYPE FUEL TYPE NOx ( CERT 0.02 0.02 0.02   OUL GASOLINE - TIER 2 UNLEADED 0.02 0.05 0.05 0.05	(g/mi) (g/mi) (g/mi) (g/mi) (mg/   GASOLINE - TIER 2 UNLEADED 0.019 0.040 0.8 1.7 0.03 0.05 *   GASOLINE - TIER 2 UNLEADED 0.026 0.055 1.0 2.1 0.06 0.07 *   GASOLINE - TIER 2 UNLEADED 0.026 0.055 1.0 2.1 0.06 0.07 *   * * * * * * * *   6ASOLINE - TIER 2 0.026 0.055 1.0 2.1 0.06 0.07 *   * * * * * * * *   50K GASOLINE - TIER 2 UNLEADED 0.02 0.07   OUL GASOLINE - TIER 2 UNLEADED 0.05 0.09	$ \begin{array}{c c c c c c c c c c } & (g/mi) & (g/mi) & (g/mi) & (mg/mi) \\ \hline $	(g/mi) (g/mi) (g/mi) (mg/mi)   CERT STD STD CERT STD CERT STD CO (g ST ST ST ST	

			SFT	PEXHAL	ST EM	SSION	STANDA	RDS A	ND C	ERTIFIC	ATION LE	EVELS		
A AND A					U	IS06	_			SC03		CC	MPOSITE	
	FUEL TYPE			NMHC+N (g/mi)	-	CO (g/mi)	PN (mg/i			C+NOx mi)	CO (g/mi)	NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
GASOLI		NE C	ERT	0.07		1.4 10.5		- 13 Labra I	0.03		1.3			
6	- TIER UNLEADI	_	STD	0.25				2. 21.			3.5			
		C	ERT	*		*	* *		* *		*	*	*	*
@ UL	*		STD	*		*	* *			*	*	*	*	*
			BIN	a ling and	1.4.1		2.8.4		a the state	11		*		in Parting
		WHO	LE VEH	ICLE EV	APORA	TIVE EN	ISSION	STAN	DARD	S AND O	CERTIFIC	ATION LEVE	LS	
					W	IOLE VI	HICLE	VAPO	RATI	VE TEST	TING			
	ORATIVE	FUEL TYPE		3DHS (g/test) @ UL				2DHS (g/test) @ UL			RL (g/mi) @ UL			
				CER	TS	TD	FEL	CER	T	STD	FEL	CEF	CERT	
GFMXR0125NBV		Т	SOLINE TIER 2 NLEADED	0.3	0.31 0.0		*	0.2	26 0.85 *		0.0	00	0.05	
(	ORVR / FUI	EL ON	NLY / CA	NISTER	BLEED	EVAPO	RATIVE	EMISS	SION	STANDA	RDS AND	CERTIFICA	TION LEVE	LS
								FU	EL ON	ILY EVA	P & CAN	STER BLEE	D	
EVAPORATIVE FAMILY		0	ORVR (g/gallon) @ UL						HS RIG TEST g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CA TEST (g/te	
		FUE	L TYPE	CERT STD					T	STD	CERT	STD	CERT	STD
GFMXR0125NBV		TI	LINE - LER 2 LEADED	0.01	0.20		* 1			*	*	*	*	*

California Environmental Protection Agency

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOX adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for sparkignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor: NOXS: NOX sensor; PMS; PM sensor; RDQS; reductant quality sensor; NH3S; ammonia sensor; EGR; exhaust gas recirculation; EGRC; EGR cooler: AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

# 2016 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS ENGINE (L)		TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
FORD	ESCAPE FWD	LDT2	2.5	SA6	GFMXR0125NBV	1	P	*