| O Air Resources Board | COMPANY | Medium-Duty Vehicles Page 1 of 4 |
|--|------------|--|
| California Environmental Protection Agency | FORD MOTOR | Executive Order: A-010-1932 New Passenger Cars, Light-Duty Trucks and |

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| TEST GROUP INFORMATION | | | | | | | | | | | | | | | | | |
|--|---|---------|--------|-------------------|--------|-------|------------|------|---------------------------------------|----------------|---|---------------------------|---|-----|-------------------------------|--|--|
| MODEL YEAR | | TEST G | ROUP | VEHICLE CLASS(ES) | | | | | | FUEL CATEGORY | | | FUEL TYPE | | | | |
| 2016 | 2016 GFMXD03.76BG MDV4 | | | | | | | | FLEX-FUEL VEHICLE (FFV) | | | 85% ETHANOL, GASOLINE | | | | | |
| USEFUL LIFE (miles) VEHICLE EMISSION | | | | | | | | ON (| N CATEGORY INTERIM / INT | | | ERMEDIATE IN-USE STD | | | | | |
| EXH/ORVR EVAP FTP | | | | | | | | SF | ТР | FTP | | | SFTP | | | | |
| 150 | 000 | | 15000 | 0 | LE | 2V3 I | LEV395 | | | * | | * | * | | | | |
| SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS | | | | | | | | - | OBD STATUS | | | IGINE DISPLACEMENT (L) | | | | | |
| 1 | | 217 | C, 2WR | -HO2S, | 2HO2 | 2S, 5 | SFI | | | FULL | AL | L MODELS | | | | | |
| * | | | | * | | | | - | 1 | PARTIAL | | * | 11 | | 3.7 | | |
| * | * * | | | | | | | | PAI | PARTIAL WITH * | | | | | | | |
| | | | E | VAPOF | RATIVE | 5 & R | EFUELING | (EV | AP/OF | RVR) FAMIL | / INF | ORMATION | | | | | |
| EVAP | EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO | | | | | | | GOR | RY EVAP EMISSION STD VEHICLE CLASS | | | SPECIAL FEATURES | | | | | |
| GE | MXF | 0190NB | 5 | | | LEV | V 2 | | MDV4 | | | | | * | | | |
| GF | MXR | 0190NBI | D C | | | LEV 2 | | | | MDV4 | | | * | | | | |
| | | | | | | EN | AISSION CF | EDI | T INF | ORMATION | | | | | | | |
| | | ALLOW | ANCE I | OR TE | ST GR | OUP | | | | G CREDIT FO | | NMOG CR | | FOR | OPTIONAL EXH. STD FOR WORK | | |
| BASEL | LINE | PZEV | A | T PZEV | | | TZEV | N | ON-P2 | ZEV ZERO-E | VAP | | DR | | TRUCKS | | |
| | * * * | | | | | | | | N | | | 1 | N N | | | | |
| | NMOG AND FLEET AVERAGE INFORMATION | | | | | | | | | | | | | | | | |
| NMOG RAF CH4 RAF FTP NMO RATIO (G | | | | | | | | | CRATIO DC+ | | NMOG+NOX FLEET STD PC+LDT (0-3750 LVW) (g/mi) | | NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi) | | | | |
| * | | * | | 1.3 | 10 | | ŀ | | | | * | | | | * | | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. California Environmental Protection Agency

OB Air Resources Board

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of July 2015.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

FUEL TYPE

Om Air Resources Board

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

| | | | | | NMOG+NOx (g/mi) | | | CO (g/mi) | | | | Ox mi) | | HCł (mg/ | | | PM (g/mi) | | |
|---|------|--|-------|-----------------------------|--------------------|-------------------------|-------------|--------------|---------------|-------------|--------------------|--------------|--------------|-------------------|--|----------------|--------------|---------------|--|
| in an | | | | CE | RT | STD | CE | RT | STD | C | ERT | STD | CER | T | STD | CE | RT | STD | |
| FTP@5 | OK | | * | | * | * | | * | * | | * | * | * | | * | | * | . * | |
| FTP@UL (GASO | | -EPA DLINE- E10) | | 0.1474 0.3 (0.1335) (0.3 | | | .74 .34) | 6.4 (6.4) |) (0 | * .070) | * (*) | 1.7 | | 6 (6) | * (0.003) | | 0.12 (0.12) | | |
| 50°F @4K | | E85-EPA | | 0. | 714 | 0.790 | 1. | .77 | 6.4 | 0 | .014 | * | 2.6 | 5 | 64 | the state and | | ni. j | |
| | | | | - | | | | | | -1 | NA | OG+N | Ox (g/mi) | _ | | CO | (g/mi) | | |
| | | a da la constante da la consta | | | F | UEL T | PE | | | ſ | CERT | | STD | | CERT | | | STD | |
| HWFE | T@: | 50K | | | | * | | | | | 1 | | * | | | | | | |
| HWFE | т@ | UL | | | | E85-E INE-L | | 3 E10) | | | 0.0913 (0.1085) | | 0.395 | | | | C. 6.4 | | |
| 20°F | @ 50 | K | | | | * | | | | | | 「大学 | | 200 | * | | | * | |
| | - | - | | SFT | PEXH | UST | MISSI | ON S | TANDA | RDS A | ND CI | ERTIFIC | ATION L | EVE | LS | | | | |
| - 24 | | | | - 31 | | | US06 | | | T | | SC03 | | 1 | | OMPC | SITE | | |
| α - καθα' = - Ξ = " | FUE | EL TY | PE | | MOG- | | CC (g/n | | PM (mg/r | | NMOG (g/i | s+NOx mi) | CO (g/mi) | NMOG+NC (g/mi) | | x CO (g/mi) | | PM (mg/mi) | |
| | | * | | CERT * * | | in an the second second | | * | | * | | | | | and a state of the | | | | |
| @ 4K | | | | TD | * | * | | * 24 4 4 | | | * | | * | 1 | | | 14 2 C | | |
| | | | | CERT * | | * | * * | | | * | | * | * | | | * | * | | |
| @ UL | | | | * STD * | | * | | * | | 1 | e | * | * | | | * | * | | |
| | | | BIN | | | | | | | | | | | * | | | | | |
| | | | WHOL | E VEH | ICLE E | VAPO | RATIVE | EEMI | SSION S | STAN | DARDS | SANDO | ERTIFIC | ATIC | ON LEVE | LS | | | |
| | | | | | | | NHOLI | E VEH | ICLE E | VAPC | RATI | /E TEST | ING | | | | | | |
| EVAPORATIVE FAMILY FUEL T | | FIFT TYPE I SUBSID | | | (g/test | ı/test) @ UL | | | 2DHS (g/test) | | @ UL | | RL (g/m | | ni) @ | ni) @ UL | | | |
| | | | | | CE | RT | STD | 1 | FEL | CER | Т | STD | FEL | _ | CE | RT | | STD | |
| GFMXF0190NBS | | | 0-EPA | | 354 | 1.00 | | * | 0.32 | | 1.25 | * | | 0.000 | | 0.05 | | | |
| GFMXF | - | | | 0-EPA | - | 354 | 1.00 | | * | 0.32 | | 1.25 | * | | 0.0 | | 1 | 0.05 | |
| 0 | DRVF | R / FU | EL ON | _Y/CA | NISTE | R BLE | ED EV | APOR | ATIVE | | | | RDS AND | | | | LEVE | LS | |
| EVAP | ORA | TIVE | OR | VR (g/ | gallon) | @ UL | - | | | | UEL ONLY EVA | | 2DHS RIG | | | | | NISTER | |
| FAMILY | | Y | | | | | FUEL TYPE | | | /test) @ UL | | | st) @ UL | | TEST (g/te | | | | |
| | | | | TYPE | CERT | | | | | CER | T | STD | CERT | _ | STD | CEI | | STD | |
| GFMXF | | | | -EPA | 0.17 | | 0 | * | | * | | * | * | - | * | * | | * | |
| GFMXF0190NBS | | UNBS | E10 | -EPA | * | * | | * | | * | | * | * | * | | * | | * | |

OMPANY

| | | Executive Order: A-010-1932 |
|--|------------|---|
| California Environmental Protection Agency | FORD MOTOR | New Passenger Cars, Light-Duty Trucks and |
| Ø≣ Air Resources Board | COMPANY | Medium-Duty Vehicles |
| Sa Air nesources board | | Page 4 of 4 |

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for sparkignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2016 MODEL YEAR: VEHICLE MODELS INFORMATION

| MAKE | MODEL | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE FAMILY | EXH ECS | OBD | PZEV TYPE |
|------|--|-----------|---------------|------------|-----------------------|------------|-----|-----------|
| FORD | TRANSIT T150 VAN FFV | MDV4 | 3.7 | SA6 | GFMXR0190NBD | 1 | F | * |
| FORD | TRANSIT T250 CHASSIS CAB 2WD FFV | MDV4 | 3.7 | SA6 | GFMXF0190NBS | 1 | F | * |
| FORD | TRANSIT T250 CUTAWAY 2WD FFV | MDV4 | 3.7 | SA6 | GFMXF0190NBS | 1 | F | * |
| FORD | TRANSIT T250 VAN 2WD FFV | MDV4 | 3.7 | SA6 | GFMXR0190NBD | 1 | F | * |
| FORD | TRANSIT T250 WAGON 2WD FFV | MDV4 | 3.7 | SA6 | GFMXR0190NBD | 1 | F | * |
| FORD | TRANSIT T350 CHASSIS CAB 2WD FFV | MDV4 | 3.7 | SA6 | GFMXF0190NBS | 1 | F | * |
| FORD | TRANSIT T350 CUTAWAY 2WD FFV | MDV4 | 3.7 | SA6 | GFMXF0190NBS | 1 | F | * |
| FORD | TRANSIT T350 VAN 2WD FFV | MDV4 | 3.7 | SA6 | GFMXR0190NBD | 1 | F | * |
| FORD | TRANSIT T350 WAGON 2WD FFV | MDV4 | 3.7 | SA6 | GFMXR0190NBD | 1 | F | * |