| | | Executive Order: A-006-1980 |
|--|----------------|---|
| California Environmental Protection Agency | GENERAL MOTORS | New Passenger Cars, Light-Duty Trucks and |
| Air Resources Board | LLC. | Medium-Duty Vehicles |
| C All nesources board | | Page 1 of 4 |
| | 1 | 1 |

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| | | | | | - | TEST G | ROU | P IN | IFOR | MATION | | | | | | |
|--------------------------------------|--|--------|---------|----------------|---------------------------------------|-------------|--------|---|---------------------------------------|---|----------------|-------------------------------|---------------|--|---------------------|--|
| MOD YEA | | TEST | GROUP | | VEHICLE CLASS(ES) | | | | | FUEL CATEGORY | | | | FUEL TYPE | | |
| 201 | 6 | GGMXV0 | 2.0021 | | | PC | | | DEDICATED SINGLE FUEL VEHICLE | | | | GASOLINE | | | |
| USEFUL LIFE (miles) VEHICLE EMISSION | | | | | | | | N C | ATEGORY INTERIM / INTERMEDIATE IN-USE | | | | TE IN-USE STD | | | |
| EX | EXH/ORVR EVAP FTP | | | | | | | SF | TP | | FTP | | SFTP | | | |
| 1 | 120000 150000 | | | COU | A TIER2 BI NTED AS AR LEV2 ULEV | DASARB | | | 2 SFTP * | | | | * | | | |
| SP | ECIAL | FEATU | | CHAUS STEMS | | SION CONT | ROL | | | OBD S | TAT | US | E | NGINE | DISPLACEMENT (L) | |
| 1 | | TWC | 2), HO2 | S(2), | TC, | CAC, DFI | | | | FULL | | * | | | | |
| * | * | | | | | | | F | PARTIAL | AI | ALL MODELS 2.0 | | | 2.0 | | |
| * | * * | | | | | | | | PAF | PARTIAL WITH * FINES | | | | | | |
| | EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION | | | | | | | | | | | | | | | |
| EV | AP / OF | RVR FA | MILY | EVA | PORAT | IVE STD CA | TEGO | EGORY EVAP EMISSION STD VEHICLE CLASS SPECIAL FEATURE | | | L FEATURES | | | | | |
| | GGMXR | 013381 | .0 | | | LEV 2 | 2 PC | | | | | * | | | | |
| | GGMXR | 012081 | 8 | | | LEV 2 | 2 PC * | | | * | | | | | | |
| | | | | | | EMISSION | I CRE | DIT | INF | ORMATION | | | | | | |
| | | | VANCE F | | | | | NMOG CREDIT FOR NON-PZEV ZERO- DOR | | | r for | OPTIONAL EXH. STD FOR WORK | | | | |
| BAS | SELINE | PZEV | A | PZEV | | TZEV | | | | EVAP | | | | | TRUCKS | |
| | * | | | * | | * | | | | N | | | N | | N | |
| | | | | | NM | IOG AND FLE | EET A | VE | RAG | E INFORMA | τιοι | N | | | | |
| NMO | G RAF | CH4 R | AF FT | P NMO RAT | | нсно/ | ΝМНС | R | ΑΤΙΟ | ATIO NMOG+NOX FLE PC+LDT (0-3750 (g/mi) | | -3750 LVW) LDT (37 | | NOX FLEET STD 751 LVW-8500 + MDPV (g/mi) | | |
| | * | * | | 1.0 | 04 | | * | | | | 0.0 | 93 | | 0.110 | | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. California Environmental Protection Agency

OB Air Resources Board

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED: The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961.2(a)(12) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1674 day of April 2015.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division **California Environmental Protection Agency**

FUEL TYPE

OB Air Resources Board

GENERAL MOTORS LLC.

Executive Order: A-006-1980 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

нсно

(mg/mi)

PM

(g/mi)

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

NOx

(g/mi)

| 1.1 | | | | | |
|-----|----------------------------------|------------|-------|----------|----------|
| | | NM (g/r | | C (g/ | O mi) |
| | | CERT | STD | CERT | STD |
| ok | * | * | * | * | * |
| JL | GASOLINE - TIER 2 UNLEADED | 0.0189 | 0.070 | 0.78 | 2.1 |

| | | | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD | |
|----------|-----------|----------------------------|----------|----------|----------|-----------|------------|------------|------------|------|-----------|------|--|
| FTP@50K | | * | * | * | * | * | * | * | * | * | * | * | |
| FTP@UL | FTP@UL T: | DLINE - IER 2 LEADED | 0.0189 | 0.070 | 0.78 | 2.1 0.011 | 0.011 0.04 | * | 11 | * | 0.01 | | |
| 50°F @4K | | * | * | * | * | * | * | * | * | * | | | |
| | | | | | F | | | NOx (g/mi) | | | CO (g/mi) | | |
| | No. Com | | | FUEL TYP | E CERT | | RT | T STD | | RT | STD | | |
| HWFET @ | 0 50K | | | * | | | + | + | * | CERT | | | |
| HWFET @ | DUL | GASOLINE - TIER 2 UNLEADED | | | | | 0.0 | 002 | 0.05 | | | | |
| 20°F @ | 50K | G | ASOLINE- | COLD CO | LOW OCTA | ANE | | 14 | 1 <u>.</u> | 1.8 | 35 | 10.0 | |

SETP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

| | | | | 1.000 | 11000 | A Management | Γ | 0.000 | | 0.01 | DOOITE | |
|--------------------------|----------------------------|------|------------------|--------------------|--------------------|--------------|-----------|--------------------|--------------|--------------------|--------------|--------------|
| | | | · · · · R. | | US06 | | | SC03 | | CON | POSITE | |
| | FUEL TYPE | | | NMHC+NOx (g/mi) | c CO (g/mi) | | M /mi) | NMHC+NOx (g/mi) | CO (g/mi) | NMHC+NOx (g/mi) | CO (g/mi) | PM (mg/mi |
| | GASOLIN | VE C | CERT | 0.045 | 1.94 | | - 1 | 0.012 | 0.86 | | | |
| @4K - TIER 2 UNLEADED | | | STD | 0.14 8.0 | | 1.7% | | 0.20 | 2.7 | | | |
| @ UL | | | CERT | | * | | * | * | * | * | * | * |
| | * | | STD | * | * * | | * | * | * | * | * | * |
| - | | Г | BIN | | 1.2.2 | | | | | * | - | |
| | | WHO | LE VE | HICLE EVAP | ORATIVE E | MISSION | STAN | DARDS AND | CERTIFIC | ATION LEVELS | S | |
| | | | | | WHOLE | VEHICLE | EVAPO | DRATIVE TES | TING | PI | (g/mi) @ | 10 |
| | | | | PE 3Dł | 3DHS (g/test) @ UL | | | 2DHS (g/test | | (g/iii) @ | UL | |
| | | | | CERT | STD | FEL | CER | T STD | FE | L CERT | | STD |
| GGMXI | GMXR0120818 GASOLI PHAS | | OLINE- HASE 2 | 0 343 | 0.50 | * | 0.58 | 0.65 | * | 0.000 | D | 0.05 |
| CCMYP0133810 | | | OLINE- | 10 205 | 0.50 | * | 0.28 | 0.65 | * | 0.000 | D | 0.05 |

| California Envi O Air R | | | | GENERAL LL | | 1 | Executive Order: A-006-1980 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4 | | | | | | | |
|--|---|---|---|---|---|--|---|--|---|---|--|--|--------------------------------------|--|
| ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS | | | | | | | | | | | | | | |
| EVAPORATIVE FAMILY | ORVR (g/gallon) @ UL | | ORVR (g/gallon) @ UL | | | | FUEL TYPE | 3DHS RIG T | | TEST 2DHS RIG TEST | | | BLEED CANISTER TEST (g/test) @ 4K | |
| | FUEL TYPE | CERT | STD | 1 | CERT | STD | CERT | STD | CERT | STD | | | | |
| GGMXR0133810 | GASOLINE- OTH | 0.011 | 0.20 | * | * | * | * | * | * | * | | | | |
| GGMXR0120818 | GASOLINE- OTH | 0.025 | 0.20 | * | * | * | * | * | * | * | | | | |
| *: not applicable; # LDT<6000#GVWR 8500#ALVW; MDV duty passenger ve vehicle weight ratir super ULEV; ZEV: TWC/OC: 3-way/or adsorption catalyst; ignited engine; HO sensor; PMS: PM s cooler; AIR/AIRE: DFI/IFI: direct/indir diagnostic; DOR: c CNG/LNG: compre ethanol ("90%"gas continuously varial automated manual | 4,3751-5750#L /: medium-duty hicle; ECS: em ng; LVW: loade zero-emission xidizing catalys t; SCR-U or SC CTOX/PTOX: 2S/02S: heate secondary air ect fuel injectio direct ozone re essed/liquefied oline) fuel; A: a ole transmissione | VW; LDT vehicle; ission ca ed vehicle; vehicle; st; ADST CRC/SCF continuo ed/oxyge : reducta injection on; TC/S ducing; F natural automatio on; SCV: | F3: LDT MDV4: ontrol sy e weigh PZEV: WC: ad R-N or S us/peric on senso int quali (belt dri C: turbo HCT: hy gas; LP c (with la selectal | 6001-8500#GVM MDV 8501-1000 vstem; CERT: cer t; ALVW: adjusted partial ZEV; AT F sorbing TWC; HA CRC-NH3: selec odic trap oxidizer; or; WR-HO2S or A ty sensor; NH3S: ven)/(electric driv /super charger; C drocarbon trap; B G: liquefied petrol ockup); M: manu ble continuously | /R,3751-57 0#GVWR; tification; S d LVW; LEV 2ZEV: adva C: HC ads tive catalyti DPF: diese AFS: wide r ammonia s en); PAIR: CAN: bleed leum gas; E al transmis variable trai | 50#ALVW; MDV5: MD TD: standa /: low emis nced techn orbing cata ic reduction el particulat ange/linear sensor; EGI pulsed AIR e air cooler d carbon ca 585: "85%" sion; SA: si | LDT4: LDT V 10001-14 Ird; FEL: fai sion vehicle ology PZEV lyst; WU: w a-urea/amm e filter (acti t/heated air- R: exhaust ; SFI/MFI: ; SFI/MFI: ; F/P/\$: full/ anister; pref ethanol ("1 emi-automa | F 6001-850 4000#GVW mily emission by ULEV: ult v; TZEV: tra- varm-up cat varm-up cat ve); GPF: F fuel ratio so gas recircu sequential/part ix 2: paralle 5% "gasolin atic transmi | 0#GVWR,5 R; MDPV: r on limit; GV tra LEV; SL ansitional Z alyst; NAC: DC: ammon PM filter for ensor; NO2 lation; EGR multiport fue ial with fine el; (2) suffix e) fuel; E10 ssion; CV: | 751- medium- WR: gross JLEV: EV; NOx ia spark- XS: NOx RC: EGR el injection; s on-board : series; D: "10%" | | | | |

2016 MODEL YEAR: VEHICLE MODELS INFORMATION

| MAKE | MODEL | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE FAMILY | EXH ECS | OBD | PZEV TYPE |
|-------|-----------|-----------|---------------|------------|-----------------------|------------|-----|-----------|
| BUICK | REGAL | PC | 2.0 | M6, SA6 | GGMXR0133810 | 1 | P | * |
| BUICK | REGAL AWD | PC | 2.0 | SA6 | GGMXR0133810 | 1 | P | * |
| BUICK | VERANO | PC | 2.0 | M6, SA6 | GGMXR0120818 | 1 | P | * |