California Environmental Protection Agency

⊘ Air Resources Board

HONDA MOTOR CO., LTD. Executive Order: A-023-0646

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION																
MODEI YEAR	TEST COOLID				VEHICLE CLASS(ES)					FUEL CATEGORY				FUEL TYPE		
2016	2016 GHNXV03.5PK3				PC					HYBRID ELECTRIC VEHICLE				GASOLINE		
USEFUL LIFE (miles)					VEHICLE EMISSION CAT				ATE	EGORY INTERIM / IN			TERMEDIATE IN-USE STD			
EXH/ORVR EVAP					FTP				SFTP			FTP			SFTP	
150000 150000					LE	v3 s	SULEV30 LEV 3			OMPOSITE	NMOG+NOX		NMOG+NOX			
SPECIAL FEATURES & EXHAUST EMI- SYSTEMS						1018	N CONTROL			OBD STATUS		ENGINE DISPLACEMEN (L)				
1	2WU-TWC, TWC, 2WR-HO2S, 2HO2S, EGR, DFI							[FULL	ALL MODELS					
*	*									PARTIAL *			3.5			
*	*							PA	RTIAL WITH FINES	*			1			
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION															
EVAP / ORVR FAMILY EVAPORATIVE STD CA						STD CATE	SORY	,	EVAP EMI: VEHICLI			SPECIAL FEATURES				
GHNXR0129VFA						LEV 2				PC			*			
						ΕN	MISSION CE	REDIT	INF	ORMATION						
ALLOWANCE FOR TEST GROUP BASELINE PZEV AT PZEV TZEV							TZEV	1		G CREDIT FOR N-PZEV ZERO- EVAP		NMOG CREDIT F		FOR	OPTIONAL EXH. STD FOR WORK TRUCKS	
	* *				*			N			N			N		
NMOG AND FLEET AVERAGE INFORMATION																
NMOG	OG RAF CH4 RAF FTP NMOG/NMHC HCHO/NMHC				HC R	ATIC	PC+LDT	NMOG+NOX FLEET STD PC+LDT (0-3750 LVW) (g/mi)		NMOG+NOX FLEET STE LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		751 LVW-8500				
*	* * 1.10 0.05				05	0.093 0.110				0.110						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

California Environmental Protection Agency

@ Air Resources Board

HONDA MOTOR CO., LTD. Executive Order: A-023-0646

New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of January 2015.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

HONDA MOTOR CO., LTD.

Executive Order: A-023-0646 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

Air Resources Board

							ΑT	TAC	НМ	ENT									
	EXHA					-						CERT				S			
	FUE	monoxio adjustm ORVR [ane; N NOx: factor C/gall	IMO oxide r; 2D on d	G: non-C es of nitr HS/3DH lispensed	CH4 orga ogen; H S [g HC d]: on-bo	anic ga CHO: /test]: pard re	as; HC: formal 2/3 day	hydrocar dehyde; F ys diurnal y vapor re	bon; NMF M: particu hot-soak covery; g: ure; SFTF	IC: no ulate r ; RL [gram	on-CH4 H matter; R g HC/mi] ; mg: mil	IC; CO: c AF: react : running ligram; m	ivity loss;			
						NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		HCHC (mg/m		-		PM (g/mi)	
			(CERT	STI	0	CERT	STE	0	CERT	STD	CERT		STD	CERT ST				
FTP@50	oĸ	*		*	*		*	*		*	*	*		* *		*			
FTP@U	11 1	OLIN V3 E1	1 0	.0241	0.0	30	0.08	1.0		*	*	0.2		4	*	0.01			
50°F @4	4K	*		*	*		*	*		*	*	*		*					
			•		HEI .	TVD	E			ı	MOG+N	Ox (g/mi)			CO (g/m	i)			
Thate was t				FUEL TYPE						С	ERT STD			CER	Τ .	STD			
HWFET @ 50K				*							* *								
HWFET @ UL				GASOLINE-LEV3 E10					0.	0.0095 0.030									
20°F (@ 50K		GAS	OLINE-C	COLD	со	LOW OC	TANE						0.41	L	10.0			
			SF	TP EXH	AUST	EM	ISSION	STAND	ARDS	AND	CERTIFIC	ATION L	EVEL	S					
				US06							SC03			COMPOSITE					
	FUEL T	YPE NI			NMOG+NOx (g/mi)		CO PI (g/mi) (mg/				G+NOx J/mi)			OG+NOx g/mi)	CO (g/mi)	PM (mg/mi			
		С		RT *			*			*		*	* "						
@ 4K	*		STD		*		*		1 .	*		*				,			
		CE		RT *		* *				*		0	.022	0.4	*				
@ UL	GASOLINE- LEV3 E10		STD	*		*		*		*		0	.110	4.2	*				
	2275	LEVS EIU B				14							0	.050					
		WH	IOLE VE	HICLE E	VAP	ORA	TIVE EN	IISSION	STA	NDAR	DS AND	ERTIFIC	ATIO	N LEVEL	S				
EVA D	OBATIVI	_				W	HOLE VE	HICLE	EVAF	PORAT	IVE TEST	TING		RI	_ (g/mi) (ล UI			
EVAPORATIVE FAMILY		FUEL TYPE			3DHS (g/test) @						S (g/test)								
							STD FEL		CERT		STD	FE	L	CER	T	STD			
GHNXR0129VFA			PHASE	SE 2			.50 *			0.294 0.6		*		0.000 0.0					
C	ORVR / F	UEL (ONLY /	CANISTE	R BL	EED	EVAPO	RATIVE				RDS AND				/ELS			
								F			UEL ONLY EVAP		& CANISTER						
EVAPORATIV FAMILY				RVR (g/gallon) (FUEL			OHS RIG TEST (g/test) @ UL		2DHS RIG (g/test) @				ED CANISTER T (g/test) @ 4K			
		FL	JEL TYP	E CER	TS	TD			CI	ERT	STD	CERT	CERT		CERT	STD			
		A !	SOLINE TIER 2 NLEADEI	0.03	6 0.	.20		*		*	*	*	*		*	*			

California Environmental Protection Agency

@ Air Resources Board

HONDA MOTOR CO., LTD. Executive Order: A-023-0646

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

*: not applicable; #: pounds; UL; useful life; PC; passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for sparkignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission: OT: other transmission

2016 MODEL YEAR: VEHICLE MODELS INFORMATION											
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE			
ACURA	RLX HYBRID	PC	3.5	SA7	GHNXR0129VFA	1	F	*			