California Environmental Protection Agency Air Resources Board

MITSUBISHI MOTORS CORPORATION

Executive Order: A-086-0351

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

							TEST GRO	UP II	NFO	RMATION				•		
MODEL YEAR		TEST GROUP			VEHICLE CLASS(ES)					FUEL CATEGORY		FUEL TYPE				
2016	GMTXT03.0G5P				LDT2							SINGLE FUEL		GASOLINE		
USEFUL LIFE (miles)				V	VEHICLE EMISSION				CATEGORY INTERIM / INT			TERMEDIATE IN-USE STD				
EXH/ORVR EVAP				FTP				SFTP			FTP		SFTP			
150	000		15000	0	LE	v3 t	JLEV70	LEV	3 C	COMPOSITE		NMOG+NO	K	NMOG+NOX		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL OBD STATUS									ENGINE DISPLACEMENT (L)							
1	2WU-	-TWC, I	TWC, 2W	R-H02	S, 2H	02S,	EGR, SF	[FULL	AL	L MODELS				
*				* PARTIAL * 3.0						3.0						
*				* PARTIAL WITH * FINES												
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION																
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO						GORY	Y EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES						
GMTXR0135A1D					LEV 2					LDT2			*			
						ΕN	MISSION C	REDI	T INF	ORMATION						
ALLOWANCE FOR TEST GRO					ROUP			NMOG CREDIT FO		THE NAME OF THE PROPERTY OF TH		T FOR	STD FOR WORK			
BASEL	BASELINE PZEV			T PZEV	1		TZEV		EVAP						TRUCKS	
	*			*		*		N		N		ſ		N		
NMOG AND FLEET AVERAGE INFORMATION																
NMOG F	RAF CH4 RAF FTF			NMOG/NMHC RATIO		HCHO/NMHC RA		ATIC	TIO PC+LDT (OX FLEET STD (0-3750 LVW) g/mi)		NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)			
*		*		1.	10		0.0	010			0.0	.093		0.110		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

California Environmental Protection Agency

⊘ Air Resources Board

MITSUBISHI MOTORS CORPORATION

Executive Order: A-086-0351

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

FAMILY

GMTXR0135A1D

FUEL TYPE | CERT

0.024

GASOLINE .

TIER 2

UNLEADED

Executive Order: A-086-0351

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

(g/test) @ UL

STD

CERT

(g/test) @ UL

STD

CERT

FUEL TYPE

STD

0.20

TEST (g/test) @ 4K

STD

CERT

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP **FUEL TYPE** NMOG+NOx CO **HCHO** PM NOx (g/mi) (mg/mi) (g/mi) (g/mi) (g/mi) CERT STD CERT STD CERT STD CERT STD CERT STD FTP@50K * GASOLINE-0.0275 0.070 0.27 1.7 4 0.01 FTP@UL LEV3 E10 GASOLINE-* 0.0571 0.37 50°F @4K 0.140 1.7 0.3 16 LEV3 E10 NMOG+NOx (a/mi) CO (q/mi) **FUEL TYPE** CERT STD CERT STD HWFET @ 50K * 0.0096 0.070 HWFET @ UL GASOLINE-LEV3 E10 20°F @ 50K GASOLINE-COLD CO HIGH OCTANE 1.17 12.5 SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS SC03 **US06** COMPOSITE **FUEL TYPE** NMOG+NOx CO PM NMOG+NOx NMOG+NOx CO CO PM (g/mi) (g/mi) (mg/mi) (g/mi) (g/mi) (g/mi) (g/mi) (mg/mi) CERT @ 4K STD * * * CERT * * * * * 0.0332 1.66 * GASOLINE-@ UL STD 0.110 4.2 LEV3 E10 BIN 0 110 WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS WHOLE VEHICLE EVAPORATIVE TESTING RL (g/mi) @ UL **EVAPORATIVE FUEL TYPE** 3DHS (g/test) @ UL 2DHS (g/test) @ UL **FAMILY** CERT STD FEL CERT STD FEL CERT STD GASOLINE-CA GMTXR0135A1D 0.121 0.65 0.140 0.85 0.012 0.05 PHASE 2 ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS **FUEL ONLY EVAP & CANISTER BLEED** ORVR (g/gallon) @ UL **EVAPORATIVE 3DHS RIG TEST** 2DHS RIG TEST **BLEED CANISTER**

California Environmental Protection Agency

⊘ Air Resources Board

MITSUBISHI MOTORS CORPORATION

Executive Order: A-086-0351

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT; light-duty truck; LDT1; LDT<6000#GVWR,0-3750#LVW; LDT2; .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for sparkignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix; series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission: OT: other transmission

2016 MODEL YEAR: VEHICLE MODELS INFORMATION											
MAKE	MODEL	VEH CLASS	ENGINE TRANS TY		EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE			
MITSUBISHI	OUTLANDER	LDT2	3.0	SA6	GMTXR0135A1D	1	F	*			