California Environmental Protection Agency

NISSAN MOTOR COMPANY, LTD.

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRC	UP IN	IFO	RMATION							
MODI YEA	1 1	EST G	ROUP	VEHICLE CLASS(ES)					FUEL CATEGORY				FUEL TYPE			
201	6 GN	GNSXT02.5G5D LDT1, LDT2						DEDICATED SINGLE FUEL VEHICLE				GASOLINE				
	USEFUL	LIFE	(miles)	T		/EHICLE EMISS	EMISSION CATEGORY INTERIM / INTERMEDIATE IN-					E IN-USE STD				
EX	EXH/ORVR EVAP					FTP		SFTP			FTP			SFTP		
1	120000 150000				I	LEV2 ULEV	I		2 SFTP NDARD		*			*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							L		OBD S	BD STATUS		ENGINE DISPLACE (L)				
1	,	TWO	C(2),WR-	HO2S	, но2	S, SFI			FULL	*						
*				*					PARTIAL		*		2.5			
*	* *							PA	RTIAL WITH FINES	ALL MODELS						
			EV	APOR	RATIVE	E & REFUELING	(EVA	P/O	RVR) FAMIL	Y INF	ORMATION	1				
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO							GORY	(		EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
GNSXR0120PBB						LEV 2			LI	OT1			*			
						EMISSION C	REDI	T INF	ORMATION							
	A	LLOW	ANCE FC	RTE	ST GR	OUP		NMOG CREDIT FOR NMOG CREDIT FOR			FOR	OPTIONAL EXH. STD FOR WORK				
BAS	BASELINE PZEV AT PZEV					TZEV	NC	NON-PZEV ZERO-EVAP D				JR	TRUCKS			
* * *							N N					N				
	NMOG AND FLEET AVERAGE INFORMATION															
NMOG RAF	INMOG/NMHC			O/NMI ATIO	PC+LDI (			/W)   LDT	(375	X FLEET ST 1 LVW-8500 MDPV (g/mi		MDV	NOX FLEET STD (10001-14000 /WR) (g/mi)			
*	*		1.04		*	* 0.093 0.110 *					*					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of

California Environmental Protection Agency

### OB Air Resources Board

NISSAN MOTOR COMPANY, LTD. Executive Order: A-015-0707-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

### BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBO) system of the listed vehicle models has been determined to have five deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$75 per vehicle for the third through fifth deficiencies for vehicles in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2016 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-015-0707 dated August 27, 2015.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_day of May 2016.

Annette Hebert, Chief

**California Environmental Protection Agency** 

OB Air Resources Board

FUEL TYPE

Executive Order: A-015-0707-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

## ATTACHMENT

### EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

ALC: No.													
			NMOG (g/mi)			CO (g/mi)		Ox mi)	HCI (mg			PM (g/mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CER	T STD	
FTP@50K	TP@50K GASOLINE CA PHASE		0.010	0.040	0.4	1.7	0.01	0.05	*	* 8		*	
FTP@UL	TP@UL GASC		0.011	0.055	0.4	2.1	0.01	0.07	*	11	*	0.01	
50°F @4K		*	*	*	*	*	*	*	. *	*			
					E		NOx (g/mi)			CO (g/mi)			
			FUEL TYP	CE	RT	STD	CERT		STD				
HWFET @ 50K			NE - CA	0.	0.01 0.07								
HWFET @ UL			NE - CA	0.	01	0.09							
20°F @ 50K		G	ASOLINE-	COLD CO	LOW OCT	ANE				1.	2	10.0	

#### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

-			SFT	PEXHAL	JST EM	ISSION	STAND	ARDS	AND	CERTIFIC	ATION L	EVELS				
					1	JS06				SC03		C	OMPO	SITE		
	FUEL TYPE			NMHC+NOx (g/mi)		CO PM (g/mi) (mg/mi)				IC+NOx g/mi)	CO (g/mi)	NMOG+N (g/mi)		CO /mi)	PM (mg/mi)	
@4K	GASOLINE - CA PHASE 2		CERT	0.03		3.2	2		0.005		0.4					
ent			STD			8.0				0.20	2.7					
			CERT *			*			*		*	*	*		*	
@ UL	*		STD		*		* *			*	*	*		*	*	
			BIN						11月1日 日本			*			Plante Part	
		WH	OLE VEH	ICLE EV	APORA	TIVE E	MISSION	STAN	IDAR	DS AND O	CERTIFIC	ATION LEV	ELS			
					W	HOLE V	EHICLE	EVAP	ORAT	IVE TEST	TING					
	EVAPORATIVE FAMILY		FUEL TYPE		DHS (g	g/test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @ Ul			UL	
				CEF	RT :	STD	FEL	CEF	RT	STD	FEI	_ CI	ERT	STD		
GNSXR0120PBB		1	SOLINE PHASE	104	6 0	. 65	*	0.4	13	0.85	*	0.	001	0.05		
(	ORVR / FUI	EL C	DNLY/CA	NISTER	BLEED	EVAP	ORATIVE	EMIS	SION	STANDA	RDS AND	CERTIFIC	ATION	LEVE	LS	
						-		FL	JEL C	NLY EVA	P & CAN	STER BLE	ED			
EVAPORATIVE		ORVR (g/gal		gallon) (	lon) @ UL		FUEL TYPE		OHS RIG TEST (g/test) @ UL			RIG TEST st) @ UL			ANISTER est) @ 4K	
		FU	EL TYPE	CERT	STD			CE	RT	STD	CERT	STD	CER	T	STD	
GNSXI	R0120PBB	Т	OLINE - IER 2 LEADED	0.06	0.20		*		r	*	*	*	*		*	

California Environmental Protection Agency	NISSAN MOTOR COMPANY, LTD.	Executive Order: A-015-0707-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4
LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 600 8500#ALVW; MDV: medium-duty vehicle; MDV4: ME duty passenger vehicle; HDV: heavy-duty vehicle; E0 emission limit; GVWR: gross vehicle weight rating; L ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-er TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing ca catalyst; NAC: NOx adsorption catalyst; SCR-U or S0 NH3OC: ammonia oxidation catalyst; CTOX/PTOX: of filter for spark-ignited engine; HO2S/O2S: heated/oxy NOXS: NOx sensor; PMS: PM sensor; RDQS: reduce EGRC: EGR cooler; AIR/AIRE: secondary air injection fuel injection; DFI/IFI: direct/indirect fuel injection; TC fines on-board diagnostic; DOR: direct ozone reducir suffix: series; CNG/LNG: compressed/liquefied natur E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic	01-8500#GVWR,3751-5750 DV 8501-10000#GVWR; MI CS: emission control system VW: loaded vehicle weight; nission vehicle; PZEV: part atalyst; ADSTWC: adsorbin CRC/SCR-N or SCRC-NH3 continuous/periodic trap oxi ygen sensor; WR-HO2S or tant quality sensor; NH3S: on (belt driven)/(electric driv //SC: turbo/super charger; ( ng; HCT: hydrocarbon trap; al gas; LPG: liquefied petro ic (with lockup); M: manual continuously variable transi	DV5: MDV 10001-14000#GVWR; MDPV: medium- n; CERT: certification; STD: standard; FEL: family ALVW: adjusted LVW; LEV: low emission vehicle; ial ZEV; AT PZEV: advanced technology PZEV; g TWC; HAC: HC adsorbing catalyst; WU: warm-up s: selective catalytic reduction-urea/ammonia; dizer; DPF: diesel particulate filter (active); GPF: PM AFS: wide range/linear/heated air-fuel ratio sensor; ammonia sensor; EGR: exhaust gas recirculation; en); PAIR: pulsed AIR; SFI/MFI: sequential/multiport CAC: charge air cooler; F/P/\$: full/partial/partial with

# 2016 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
NISSAN	ROGUE FWD	LDT1	2.5	CV1	GNSXR0120PBB	1	\$	*
NISSAN	ROGUE FWD	LDT2	2.5	CV1	GNSXR0120PBB	1	\$	*