California Environmental Protection Agency

⊘ Air Resources Board

NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0725

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
	MODEL YEAR TEST GROUP				VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
201	6	GNSXT03	3.5G7B		LDT2			DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEF	UL LIFE	(miles)		VEHI	LE EMISSION CATEGORY INTERIM / INT					TERMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP			SFTP			FTP S		
150000 150000]	LEV3 ULEV125 LEV 3 (COMPOSITE *			NMOG+NOX		
SPE	CIAL	FEATUR		HAUST EN	T EMISSION CONTROL			OBD STATUS			ENGINE DISPLACEMENT (L)		
1	2TWC, 2WR-HO2S, 2HO2S, TWC, SFI FULL ALL MODELS												
*	* PARTIAL * 3.5								3.5				
*	* PARTIAL WITH * FINES												
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	EVAP / ORVR FAMILY EVAPORATIVE STE						TD CATEGORY EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES		
GNSXR0120PBB LET					V 2		LI	OT2		*			
					E	MISSION CF	REDIT INF	ORMATION					
		ALLOW	ANCE FO	R TEST G	ROUP	7		NMOG CREDIT FOR NMOG CR			ISTD FOR WOR		
BAS	PZEV	TA	PZEV	TZEV		NON-P	NON-PZEV ZERO-EVAI		DC	OR	TRUCKS		
	* * *					N I			И				
NMOG AND FLEET AVERAGE INFORMATION													
NMOC	MOG RAFICHARAFI		NMOG/NI RATIO	I HCHO/NMH(HC RATIO	PC+LDT	NMOG+NOX FLEET STD PC+LDT (0-3750 LVW) (g/mi)		NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)			
1	* 1.10 *				ŀ	0.093 0.110							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

California Environmental Protection Agency

⊘ Air Resources Board

NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0725

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

NISSAN MOTOR COMPANY, LTD. Executive Order: A-015-0725

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

	EXHA	UST	AND	EVAF	PORA	TIVE	EMIS	SION	STAN	IDAR	DS ANI	CER1	IFIC	ATION	LEV	ELS		
		EXH	AUST EN	MISSIG	ON ST	ANDA	RDS AN	ID CER	TIFICA	TION	LEVELS	(FTP, HV	VFET	, 50°F, 2	0°F)			
	4	C m ai		CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP														
				NMOG+NOx			CO			NOx			НСНО			PM		
	14			(g/mi)			((g/mi)		(g/mi)			(mg/			(g/mi)		
			C	CERT	S	TD	CERT	ST	D	CERT	STO	CE	RT	STD	CEF	RT	STD	
TP@5)K	*		*		*	*	*		*	*	*		*	*	*		
FTP@L		OLIN 3 E	1 ()	.041	0.	125	0.6	2.	1	*	(*)	1		4		* 0		
50°F @4	1K	*		*		*	*	*		*	*	*		*	0.70		- 15T - 15 東京	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	109 11				FUE	TVD	_			N	IMOG+N	Ox (g/mi)			CO (g	g/mi)		
				FUEL TYPE						CERT STD)	CERT			STD	
HWFE	@ 50K					*					*	*	*					
HWFE	T@UL			GAS	OLINE	E-LEV	V3 E10		0.	.006	0.125		F.					
20°F	@ 50K		GASC	LINE	-COLI	co	LOW OC	TANE	1					1.	4		12.5	
		-	SF	TP EX	HAUS	TEM	ISSION	STAND	ARDS	AND (CERTIFIC	ATION L	EVE	LS				
				US06						SC03			T	COMPOSITE				
	FUEL TYPE		, 1.41.1 <u>2</u>	NMOG+NOx (g/mi)		CO PM (g/mi) (mg/mi)			NMOG+NOx (g/mi)		CO (g/mi)			MOG+NOx (g/mi) (g		PM (mg/mi)		
			CERT		*		*	*			*		*				T-Fall	
@ 4K	*		STD		*	V	*			1	*	*	25.15		0 1.0			
			CERT	RT			*		*		*		* 0.0		0375 1.		*	
@ UL	LEV3 E10		STD		*		*	,	k		*	*		0.110	4	.2	*	
			BIN				1	1. 5						0.110	339	4	4	
		WH	OLE VE	HICLE	EVA	PORA	TIVE EN	ISSION	STAN	DAR	S AND	ERTIFIC	ATIC	N LEVE	LS			
						WI	HOLE VI	HICLE	EVAP	ORAT	IVE TEST	ring						
	ORATIVE MILY	VE FUEL TY		PE	E 3DHS (g/test) @ UL					2DHS (g/test) @			@ UL		RL (g/mi) @ UL			
				CERT S		STD FEL		CE	RT STD		FEL		CERT		S1			
GNSXR0120PBB G			SOLINE PHASE	LINE-CA ASE 2 0.38				.65 *		31	0.85	*	*		0.001		0.05	
C	RVR / FL	JEL (DNLY / C	ANIS	TER E	LEED	EVAPO	RATIVE	EMIS	SION	STANDA	RDS AN	D CE	RTIFICA	TION	EVE	LS	
			*****						FI	JEL O	NLY EVA	P & CAN	IISTE	R BLEE	D			
	ORATIVE	VE ORVE		VR (g/gallon) @						DHS RIG TEST		2DHS RIG				EED CANISTER		
FA	MILY	-				OTO	FUEL			g/test) @ UL		(g/test) (-		rest (g/test) @		
		-	EL TYPI	-	RT	STD			CE	RT	STD	CERT	-	STD	CER	1	STD	
GNSXE	0120PBE		SOLINE FIER 2 NLEADED	0.	09	0.20		*		tr	*	*		*	*		*	

California Environmental Protection Agency

OB Air Resources Board

NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0725

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV; heavy-duty vehicle; ECS; emission control system; CERT; certification; STD; standard; FEL; family emission limit; GVWR; gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia: NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor, WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI; direct/indirect fuel injection; TC/SC; turbo/super charger; CAC; charge air cooler; F/P/\$; full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85; "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2016 MODEL YEAR:	VEHICLE	MODELS	INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
NISSAN	PATHFINDER 4WD PLATINUM	LDT2	3.5	cvì	GNSXR0120PBB	1	F	*