California Environmental Protection Agency	BAYERISCHE	Executive Order: A-008-0417-1 New Passenger Cars, Light-Duty Trucks and
OB Air Resources Board	MOTOREN WERKE AG	Medium-Duty Vehicles
		Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	FORMAT	ION	1				
MODE	-	TEST GROUP VEHICLE CLASS(ES)						FUEL CATEGORY			FUEL TYPE		
2017	017 HBMXV02.0M48					PC			CATED SINGLE FUEL VEHICLE			ASOLINE	
1	USEFUL	LIFE	(miles)	VE	HICLE EMISS	ION C	ATEGOR	Y	IN	TERIM / INT	ERMEDIA	TE IN-USE STD	
EXH	/ORVR		EVAP		FTP		SFTP	•		FTP		SFTP	
120000 150000 LE					2 ULEV	1.	EV 2 SF			. *		*	
SPE	CIAL FE	EATUR		AUST EMISS	ON CONTRO	L	1.1.2	OBD ST	TATU	s	ENGINE	DISPLACEMENT (L)	
1	WU-TW	C, TW	C, WR-HC	2S, HO2S, I	DFI, TC, CF	C	FUI	L		*			
*			•	*		1	PART	IAL	ALI	MODELS	2.0		
*			*		PARTIAL WITH *								
			EV	APORATIVE 8	REFUELING	(EVA	P/ORVR)	FAMILY	INFO	ORMATION			
EVA	P / ORV	RFAN	AILY	EVAPORATIV	E STD CATE	GORY					SPECIA	L FEATURES	
H	IBMXR01	L00F56	5	1	LEV 2	EV 2 PC					HCT		
E	IBMXR01	130F45	5	LEV 3 OPT	ION2 WITH FEL			PC			HCT		
					EMISSION C	REDIT	INFORM	ATION					
	A	LLOW	ANCE FO	R TEST GROU	JP .	N		EDIT FO	DR	NMOG CRI	DIT FOR	OPTIONAL EXH.	
BASE	ELINE P	ZEV	AT	PZEV	TZEV	NO				DO	STD FOR WOR		
	*			*	*		1	N		N	N N		
				NMO	G AND FLEE	TAVE	RAGE IN	FORMAT	TION				
NMOG/NMHC		HCHO/NMHC RATIO	PC+LDT	NMOG+NOX FLE PC+LDT (0-3750 (g/mi)		LDT (NMOG+NOX FLEET STE LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		MDV (10001-14000				
*	*		1.04	*	0	.086			0.	101		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

California Environmental Protection Agency

BAYERISCHE MOTOREN WERKE AG

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-008-0417 dated February 26, 2016.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this Z/___ day of September 2016.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

O Air Resources Board

FUEL TYPE

BAYERISCHE MOTOREN WERKE AG Executive Order: A-008-0417-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

M. Stranger												
				OG mi)	C (g/i			Ox mi)	HCH (mg/			PM (g/mi)
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	TI	DLINE - IER 2 LEADED	0.006	0.040	0.7	1.7	0.03	0.05	5 *	8	*	*
FTP@UL	TI	DLINE - IER 2 LEADED	0.007	0.055	1.0	2.1	0.03	0.07	*	11	0.00	0.01
50°F @4K	TJ	DLINE - IER 2 LEADED	0.026	0.080	0.8	1.7	0.02	0.05	5 *	16		
	inel				-			NOx (g/mi)		CO (g/	mi)
the last	- 11 -			FUEL TYP	'E		CE	RT	STD	CER	RT	STD
HWFET @ 50K		(GASOLINE	2 UNLEAD	ED	0.	01	0.07	and the second and the second			
HWFET @ UL		(GASOLINE	- TIER	2 UNLEAD	ED	0.	01	0.09			
20°F @	50K	GZ	ASOLINE-	COLD CO	HIGH OCT.	ANE				1.	6	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVE	LS
--	----

		50		US06		SCO	3	COMPOSITE		
	FUEL TYPE		NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMHC+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	GASOLINE - TIER 2 UNLEADED	CERT	0.03	0.9		0.03	0.9	iante antesato destructures caras, robus		
6		STD	0.14	8.0		0.20	2.7	1231.24		200
	L a	CERT	*	*	*	*	*	0.037	*	*
@ UL	GASOLINE - TIER 2 UNLEADED	STD	*	*	*	*	*	0.103	*	*
		BIN		Made - Kan	1 Stan Later	and Marshall	1.2020 442	0.160		

	WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS
_	

EVAPORATIVE FAMILY	FUEL TYPE		WHOLE	NG					
		3DHS (g/test) @ UL			2D	HS (g/test) (RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
HBMXR0100F56	GASOLINE - TIER 2 UNLEADED	0.10	0.50	*	*	0.65	*	0.00	0.05
HBMXR0130F45	GASOLINE- TIER3 E10	0.198	0.300	0.275	0.126	0.300	0.275	0.01	0.05

California Envi	-			BAYER MOTOREN			Executive Order: A-008-0417-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4						
ORVR / FU	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS												
EVAPORATIVE FAMILY	ORVR (g/g	gallon) @	DL 🧿	FUEL TYPE	3DHS R	ONLY EVA IG TEST) @ UL				ANISTER est) @ 4K			
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
HBMXR0100F56	GASOLINE - TIER 2 UNLEADED	0.11 0.20		*	*	*	*	×	*	*			
HBMXR0130F45	GASOLINE- TIER3 E10	0.04	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.003	0.020			
*: not applicable; # LDT<6000#GVWR 8500#ALVW; MDV duty passenger ve emission limit; GV ULEV: ultra LEV; S TZEV: transitional catalyst; NAC: NO: NH3OC: ammonia filter for spark-ignit NOXS: NOx senso EGRC: EGR coole fuel injection; DFI/I fines on-board diag suffix: series; CNG E10: "10%" ethano continuously variat automated manual	4,3751-5750#L /: medium-duty hicle; HDV: he WR: gross veh SULEV: super ZEV; TWC/OC x adsorption cata ed engine; HO r; PMS: PM se r; AIR/AIRE: se FI: direct/indire gnostic; DOR: /LNG: compre I ("90%"gasolii ole transmissio	VW; LDT v vehicle; avy-duty icle weig ULEV; Zl 2: 3-way/- atalyst; ST lyst; CTC 2S/O2S: econdary ect fuel ir direct oze ssed/liqu n; SCV:	T3: LDT (MDV4: vehicle; ht rating EV: zero oxidizing (CR-U or DX/PTO) heated/ DQS: rec v air injection; one redu efied na A: autom selectab	6001-8500#GVV MDV 8501-1000 ECS: emission of ; LVW: loaded ve -emission vehicle of catalyst; ADSTV SCRC/SCR-N of SCRC/SCR-N of Coxygen sensor; V luctant quality set ction (belt driven) TC/SC: turbo/sup licing; HCT: hydro tural gas; LPG: li matic (with lockup le continuously v	/R,3751-57 0#GVWR; I control syste action syste action syste action syste action system //C: adsorb //C: adsorb //	50#ALVW; MDV5: MD' em; CERT: ht; ALVW: a artial ZEV; / ing TWC; F 43: selectiv xidizer; DP or AFS: wid b; ammonia iven); PAIF ; CAC: cha b; BCAN: b roleum gas al transmis	LDT4: LDT V 10001-14 certificatio adjusted LV AT PZEV: a HAC: HC ac re catalytic R: pulsed P re ansor; EC R: pulsed A rge air cool leed carbol s; E85: "85% ssion; SA: s	F 6001-850 000#GVW n; STD: sta W; LEV: lo advanced te dsorbing ca reduction-u articulate fil ear/heated GR: exhaus IR; SFI/MFI ler; F/P/\$: fi n canister; f %" ethanol (emi-autom	0#GVWR,5 R; MDPV: r ndard; FEL w emission echnology F talyst; WU: rea/ammor ter (active) air-fuel rati t gas recirco l: sequentia ull/partial/pa prefix 2: pa ("15%"gaso atic transm	5751- medium- .: family vehicle; PZEV; warm-up hia; ; GPF: PM o sensor; culation; al/multiport artial with rallel; (2) bline) fuel; ission; CV:			

2017 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
MINI	MINI JOHN COOPER WORKS CLUBMAN ALL4	PC	2.0	M6 , SA8	HBMXR0130F45	1	P	*
MINI	MINI JOHN COOPER WORKS CONVERTIBLE	PC	2.0	M6 , SA6	HBMXR0100F56	1	P	*
MINI	MINI JOHN COOPER WORKS HARDTOP	PC	2.0	M6, SA6	HBMXR0100F56	1	P	*