## California Environmental Protection Agency

## **⊘** Air Resources Board

FORD MOTOR COMPANY

Executive Order: A-010-2011 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION																
MODEL YEAR	T   T	ST G	ROUP	VEHICLE CLASS(ES					FUEL	FUEL CATEGORY			FUEL TYPE			
2017	нғ	MXT02	.02JU	LDT2 DEDICATED SINGLE FUEL VEHICLE						GASOLINE						
U	SEFUL	LIFE	(miles)		VEHICLE EMISSION CATEGO				EGORY	Y INTERIM / INT				ERMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP			5	SFTP	FTP FTP		FTP			SFTP	
150	150000 150000					V3 ULEV70	ULEV70 LEV 3 COM			2	NMOG+NOX			NMOG+NOX		
OBD STATUS									DISPLACEMENT (L)							
1	TC, CAC, DFI, TWC(2), HO2S, WR-HO2S FULL *															
*				* PARTIAL ALL MODELS 2							2.0					
*				*	* PARTIAL WITH * FINES											
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION																
EVAP / ORVR FAMILY EVAPORATIVE STD CATEG							GORY	RY EVAP EMI VEHICL						SPECIAL FEATURES		
HFMXR0135NBB					LEV 2					LDT2			*			
		······································				EMISSION C	REDI	T IN	FORMATIO	N						
ALLOWANCE FOR TEST GROUP								NMOG CREDIT FOR NMOG CREDIT FOR			OPTIONAL EXH. STD FOR WORK					
BASE	LINE PZ	ZEV	AT	PZEV		TZEV	N	ON-	PZEV ZERO	J-E1	D-EVAP DOR TRUCKS					
	*			*		*			И			1	N N			
NMOG AND FLEET AVERAGE INFORMATION																
NMOG RAF					0-375		VW) L	NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi								
*	*	:	1.10		*	0	.086	5	0.101 *				*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance],

California Environmental Protection Agency

**OB** Air Resources Board

FORD MOTOR COMPANY

Executive Order: A-010-2011

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_

\_ day of October 2016

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

TIER 2

UNLEADED

HFMXR0135NBB

0.005 0.20

FORD MOTOR COMPANY

Executive Order: A-010-2011

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

							AT	TACI	НМІ	ENT							
	EXH	AUS	TANE	EV	APOR	ATIVE	EMIS	SION S	TAN	DARD	SAND	CERTI	FIC	ATION	LEVEL	S	
		EXH	AUST	EMIS	SION S	TANDA	RDS AN	ID CERT	IFICA	TION L	EVELS	FTP, HW	FET,	50°F, 20	°F)		
	FU	EL TY		mono adjust ORVF	xide; NC tment fa R [g HC/	ox: oxide ctor; 2D gallon di	es of nitr HS/3DH ispense	ogen; HC S [g HC/i d]: on-box	CHO: test]: ard re	formalde 2/3 days fueling	ehyde, P diurnal- apor red	oon; NMH M: particu hot-soak; covery; g: ure; SFTP	late i RL i gram	matter; R [g HC/mi] n; mg: mil	AF: react : running ligram; m	tivity	
						IOG+NOx (g/mi)		CO (g/mi)			Ox mi)	HCHO (mg/m				PM (g/mi)	
	-1			CEF	RT	STD	CERT	STD		CERT	STD	CER	Т	STD	CERT	STD	
FTP@50	OK	*		*		*	*	*		*	*	*		*	*	*	
FTP@U	11-1	SOLI EV3 E		0.05	502 0	.070	1.09	1.7		*	*	*		4	*	0.01	
50°F @4	4K	*		*		*	*	*		*	*	*		*			
					FUI	EL TYPI						Ox (g/mi)			CO (g/m		
		1								CE		STD		CER		STD	
HWFE1	T @ 50H	(				*				,	•	*				The state of the state of	
HWFET @ UL				GASOLINE-LEV3 E10					0.0	0.0338 0.070							
20°F @ 50K			G.F	GASOLINE-COLD CO LOW OCTANE									1.18		3	12.5	
				SFTP	EXHAL	JST EMI	SSION	STANDA	RDS	AND C	ERTIFIC	ATION LE	VEL	S			
			7 1 1	US06										MPOSIT			
	FUEL	TYPE		N	MOG+N (g/mi)		CO (g/mi)	Pi (mg/			i+NOx mi)	CO (g/mi)		OG+NOx (g/mi)	CO (g/m	PM (mg/mi	
@ 4K	1	, CE		RT *			*   1.72°			*		*	Ĭ.	3. T.	E		
	S		STD		*		*			*		*					
		CA COT TATE		ERT *		* *			*		*	0.0547		1.50	*		
@ UL							*		*	0.103		4.2	*				
			BIN							(Alak	A. 0			0.130			
		W	HOLE	VEHI	CLE EV	APORA	TIVE EN	NOISSIN	STA	NDARD:	SAND	ERTIFIC	ATIC	N LEVE	S		
						WH	HOLE V	EHICLE	EVAF	PORATI	/E TEST	ING					
	ORATIN	/E .	FUEL TYPE		TYPE 3DHS (g/f			(test) @ UL		2DHS (g/test)		@ UL		RL (g/mi		) @ UL	
					CEF	RT S	TD	FEL	CE	RT	STD	FEL	-	CEF	RT	STD	
HFMXR	R0135N		GASOLI TIEF UNLEA	2	0.3	61 0	. 65	*	0.3	336	0.85	*		0.0	0.002 0		
(	ORVR /	FUEL	ONLY	/ CAI	NISTER	BLEED	EVAPO	RATIVE	EMI	SSIONS	STANDA	RDS AND	CE	RTIFICA	TION LE	VELS	
	ORATI	/E	ORVE	R (g/g	allon) @	UL	31			HS RIG	TEST	2DHS RIG		TEST   BLEED CANISTE			
FA	MILY			VDE CERT ST		eth	FUEL TYPE			(g/test) @ UL		(g/test) (		STD CERT		/test) @ 4H	
vimarpo1 2 EVID		G2	ASOLIN	NE -					EKI SID		CERT	+	10	JEKI	310		

California Environmental Protection Agency

**⊘** Air Resources Board

FORD MOTOR COMPANY

Executive Order: A-010-2011

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

	2017 MODEL YEAR: VEHICLE MODELS INFORMATION											
MAKE	MODEL	VEH CLASS ENGIN		TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE				
FORD	EDGE AWD	LDT2	2.0	SA6	HFMXR0135NBB	1	P	*				
FORD	EDGE FWD	LDT2	2.0	SA6	HFMXR0135NBB	1	P	*				