California Environmental Protection Agency	FORD MOTOR	Executive Order: A-010-1962 New Passenger Cars, Light-Duty Trucks and
OB Air Resources Board	COMPANY	Medium-Duty Vehicles
		Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP INFO	RMATION						
MODEL YEAR	- I T H	EST G	ROUP		VEH	IICLE CLASS(E	S)	FUEL	FUEL CATEGORY			FUEL TYPE		
2017	HF	MXV02	2.0VZT			PC			D ELN EHICI	LE		GA	ASOLINE	
U	SEFUL	LIFE	(miles)		V	EHICLE EMISS	ION CAT	EGORY	I	ITERIM / IN	TER	MEDIA	TE IN-USE STD	
EXH/	ORVR		EVAP			FTP	S	FTP		FTP	/	,	SFTP	
150	0000		150000		LE	V3 SULEV30	LEV 3	COMPOSITE		PM			PM	
SPEC	CIAL FE	ATUR		IAUST TEMS	EMIS	SION CONTRO		OBD :	STAT	U,S	E	INGINE	DISPLACEMENT (L)	
1	т	WC (2)	, WR-HO	2S, H	102S,	EGR, SFI		FULL	V	*	1			
*	* * PARTIAL ALL MODELS									2.0				
*	* * PARTIAL WITH * FINES													
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVAP	P / ORV	RFAN	MILY	EVAP	ORAT	IVE STD CATE	BORY	EVAP EN VEHIC			:	SPECIAL FEATURES		
HI	FMXR01	45HCE	E	LEV	7 3 0	PTION2 WITH I	FEL		PC				нст	
				_	$\overline{\ }$	EMISSION CR	REDIT IN	FORMATION						
	A	LLOW	ANCE FO	R TES	ST GR	OUP		G CREDIT F				IT FOR	OPTIONAL EXH.	
BASE	LINE P2	ZEV	AT	PZEV		TZEV							TRUCKS	
	*		ALL	MODEL	s	*		N		1	N		N	
					NM	OG AND FLEET	AVERA	GE INFORM	ATION	1				
NMOG RAF	CH4 RAF	NMO	FTP G/NMHC ATIO	MHC RATIO PC+LDT (0-3			0-3750 L\	/W) LD1	(375	X FLEET ST 1 LVW-8500 MDPV (g/mi				
*	*	:	1.10		*	0	.086		0	.101			*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance],

California Environmental Protection Agency	FORD MOTOR	Executive Order: A-010-1962 New Passenger Cars, Light-Duty Trucks and
Air Resources Board	COMPANY	Medium-Duty Vehicles
e Air nesources board		Page 2 of 4

2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of

day of April 2016.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

FORD MOTOR COMPANY Executive Order: A-010-1962 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

A	TT.	AC	HN	ЛE	NT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

 FUEL TYPE
 CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

								-				
		NMOG+NOx (g/mi)			CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM /mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		* .	*	*	*	*	*	*	*	*	*	*
FTP@UL		LINE- 3 E10	0.019	0.030	0.4	1.0	*	*		4	*	0.003
50°F @4K		*	*	*	*	*	*	*	*	*	applant serie	all and so is a
				FUEL TYP	E		NA	IOG+NOx	(g/mi)	CO (g/mi)		
and an				FUEL ITP	E		CE	RT	STD	CER	T	STD
HWFET @	50K			*				* *				i kanada.
HWFET	WFET @ UL GASOLINE-LEV3 E1						0.011		0.030			
20°F @ 50K		GASOLIN	E - COLD	CO LOW E10	OCTANE E	PA TIEF	83			0.	4	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

- A. Syle 				US06		SC03	3	CON	POSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
em		STD	*	*		*	*			
		CERT	*	*	*	*	*	0.019	0.6	*
@ UL	DUL GASOLINE- LEV3 E10	STD	*	*	10	*	*	0.103	4.2	*
		BIN						0.040		
	WH	IOLE VE	HICLE EVAPOR	RATIVE EMI	SSION STAN	DARDS AND	CERTIFIC	ATION LEVELS	5	
				WHOLE VE	HICLE EVAP	ORATIVE TES	TING			

	FUEL TYPE		WHOLE	VEHICLE	ING					
EVAPORATIVE FAMILY		3DHS (g/test) @ UL			2D	@ UL	R	RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CER	RT	STD
HFMXR0145HCE	GASOLINE- LEV3 E10	0.175	0.300	0.300	*	0.300	0.300	0.0	00	0.05
ORVR / FUE	L ONLY / CAN	STER BLI	EED EVA	PORATIVE	EMISSIO	N STANDA	RDS AND CEF	RTIFICA	TION L	EVELS
			FUEL ONLY EVAP & CANISTER							
EVAPORATIVE FAMILY				EL TYPE		RIG TEST t) @ UL	2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K	

FAMILY				FUEL TYPE	(g/test) @ UL		(g/test) @ UL		TEST (g/test) @ 4K	
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD
HFMXR0145HCE	GASOLINE - EPA TIER3 E10 CERT FUEL	0.033	0.20	*	*	*	*	*	*	*

		Executive Order: A-010-1962			
California Environmental Protection Agency	FORD MOTOR	New Passenger Cars, Light-Duty Trucks and			
OB Air Resources Board	COMPANY	Medium-Duty Vehicle			
e Air Resources board		Page 4 of 4			
	l				

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler, AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85; "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel: A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV; selectable continuously variable transmission; AM; automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2017 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYRE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE	
FORD	FUSION HYBRID FWD	PC	2.0	CV1	HFMXR0145HCE	1	P	AT PZEV (TYPE D)	
LINCOLN	MKZ HYBRID FWD	PC	2.0	CV1	HFMXR0145HCE	1	P	AT PZEV (TYPE D)	

SIL