California Environmental Protection Agency	HONDA MOTOR CO.,	Executive Order: A-023-0649 New Passenger Cars, Light-Duty Trucks and
⊘ ■ Air Resources Board	LTD.	Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP II	NFO	RMATION						
MODE YEAR	- 1 16	ST G	ROUP	VEHICLE CLASS(ES)					FUEL	FUEL CATEGORY			FUEL TYPE		
2017	нн	NXV02	2.4YH3		PC				DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION									ATEGORY INTERIM / INTERMEDIATE IN-US				TE IN-USE STD		
EXH/ORVR EVAP						FTP		S	FTP FTP			_	SFTP		
						LEV	3	COMPOSITE		*		NMOG+NOX			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS									OBD	STAT	US		ENGINE	DISPLACEMENT (L)	
1	W	U-TWC	C, TWC,	WR-H	02S,	HO2S, DFI			FULL		*				
*	*								PARTIAL	A	LL MODELS			2.4	
*	* PARTIAL WITH * FINES								*	1					
			EV	APOF	ATIVE	& REFUELING	(EV/	AP/C	RVR) FAMIL	Y IN	FORMATION				
EVA	P / ORV	R FAN	AILY	EVAF	ORAT	IVE STD CATE	GOR	(EVAP EN VEHIC				SPECIA	L FEATURES	
н	HNXR01	21VF7	A I			LEV 2			PC *			*			
						EMISSION CI	REDI	T IN	FORMATION						
	А	LLOW	ANCE FO	OR TE	ST GR	OUP								OPTIONAL EXH. STD FOR WORK	
BASE	LINE PZ	ZEV	AT	PZEV		TZEV	EV NON-PZEV ZERO-EV			EVAI	EVAP DOF			TRUCKS	
	*			*		*		N			N N				
					NM	IOG AND FLEET	AVE	RA	GE INFORM		N				
NMOG RAF	NMO(3/NMH(2)) P(1+1) (0-3)				0-375	50 LVW) LDT (3751 LVW-8500 MDV (NOX FLEET STD (10001-14000 /WR) (g/mi)						
*	*	:	1.10	(0.05	0	.086		-		0.101			*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance],

California Environmental Protection Agency	HONDA MOTOR CO.,	Executive Order: A-023-0649 New Passenger Cars, Light-Duty Trucks and
OB Air Resources Board	LTD.	Medium-Duty Vehicles
		Page 2 of 4

2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this <u>24</u> day of May 2016.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

FUEL TYPE

HONDA MOTOR CO., OB Air Resources Board

Executive Order: A-023-0649 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

LTD.

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

A AND A		- 111														
	* 1			NMOG+I (g/mi			CO J/mi)		N((g/i	Dx mi)		HCH mg/n			PN (g/n	
			CI	ERT	STD	CERT	ST	o c	ERT	STD	CER	т	STD	CER	Т	STD
TP@5	ok	*		*	*	*	*		*	*	*		*	*		*
FTP@L		OLINI 3 E1	1 0	020	0.125	0.1	2.1	1	*	*	*		4	*		0.01
50°F @	4K	*		*	*	*	*		*	*	*		*			
A SAR				FU	EL TYP	=			NN	IOG+NC)x (g/mi)	CO (g/mi			/mi)	
5. 18 ⁻¹ . 19				FU		-			CE	RT	STD		CER	RT		STD
IWFE	T @ 50K				*				*		*					
HWFE	T@UL			GASOLI	NE-LEV	3 E10			0.0	05	0.125	;				
20°F	@ 50K		GASO	LINE-CO	LD CO	LOW OCT	TANE					in the second	0.	7	1	L0.0
			SFT	PEXHA	UST EM	ISSION S	STANDA	ARDS A	ND CE	RTIFIC	ATION LE	EVEL	S			
					L	JS06	1			SC03				OMPOS		
	FUEL T	PE		NMOG+I (g/mi		CO (g/mi)	Pi (mg		NMOG (g/r		CO (g/mi)		NMOG+NOx (g/mi)		O mi)	PM (mg/mi
@ 4K	(*		CERT	*		*			*		*					
			STD	*		*			*		*	*				
		CE		*		*	* * *		*	0.024		0.	. 1	*		
@ UL	BIN		STD	*		*	1		*		*	0	0.103	4.	.2	*
												0.100				
		WH	OLE VEH	ICLE EV	APORA	TIVE EN	ISSION	STAN	DARDS	AND C	ERTIFIC	ATIO	N LEVE	LS		
				-	W	HOLE VE	HICLE	EVAPC	RATIV	E TEST	ING					
		F	UEL TYP	PE 3DHS (g/test) @ UL					2DHS (g/test) @ UL				RL (g/mi) @ UL			
				CE	RTS	TD	FEL	CER	т	STD	FEL	-	CE	RT		STD
HHNXR0121VFA			ASOLINE A PHASE	10	38 0	.50	*	0.3	7	0.65	*		0.00		0.05	
C	DRVR / FL	JEL C	DNLY / CA	ANISTER	BLEED	EVAPO	RATIVE	EMISS	SION S	TANDA	RDS AND	CE	RTIFICA	TIONL	EVE	LS
								FU	EL ON	LYEVA	P & CAN	STE	R BLEE	D		
			ORVR (g/	/R (g/gallon) @ UL						DHS RIG TEST g/test) @ UL					BLEED CANIS TEST (g/test) @	
		FU	EL TYPE	CERT	STD			CEF	RT	STD	CERT		STD	CER	CERT	
HHNXR0121VFA		. 3	SOLINE - TIER 2 VLEADED	0.03	0.20		*			*	*	*		*		*

California Environmental Protection Agency	HONDA MOTOR CO., LTD.	New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Ø≣ Air Resources Board	LID.	Page 4 of 4

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW: LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV: TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler: AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2017 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
HONDA	ACCORD	PC	2.4	M6	HHNXR0121VFA	1	P	*