## California Environmental Protection Agency

@ Air Resources Board

HONDA MOTOR CO., LTD. Executive Order: A-023-0653-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP IN	FORMAT	ION					
MODE	- I T	TEST GROUP			VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
2017 HHNXV03.5VH3				DEDICATED SINGLE FUEL VEHICLE			GASOLINE						
l	JSEFUL	LIFE	(miles)	V	EHICLE EMISS	SION C	ATEGOR	Y	IN	TERIM / INT	ERMEDIA	TE IN-USE STD	
EXH/ORVR EVAP					FTP			SFTP		FTP	SFTP		
150000 150000				LEV	3 ULEV125	V125 LEV 3 COMPOSITE		SITE	*		NMOG+NOX		
SPE	CIAL FE	ATUR		AUST EMIS	SION CONTRO	DL		OBD ST	TATU	IS	ENGINE	DISPLACEMENT (L)	
1 2WU-TWC, TWC, 2WR-HO2S, 2HO2S, EGR, DFI							FULL		*				
*	*							PARTIAL A		MODELS	3.5		
*			*		PARTIA			*					
			EV	APORATIVE	& REFUELING	(EVA	P/ORVR)	FAMILY	INF	ORMATION	1		
EVAP / ORVR FAMILY EVAPORATIVE STD (						STD CATEGORY EVAP EMIS VEHICLE				SPECIAL FEATURES			
HHNXR0151VFA LI					LEV 2	EV 2			PC		*		
					EMISSION C	REDIT	INFORM	ATION	***************************************		~~~		
	A	LLOW	ANCE FO	R TEST GRO	DUP		MOG CR			NMOG CRE		OPTIONAL EXH STD FOR WORK	
BASELINE PZEV AT PZEV					TZEV	NON-PZEV ZERO-E			EVAP DOF		R	TRUCKS	
* *					*	N				N		N	
				NM	OG AND FLEE	TAVE	RAGE IN	FORMA	TION				
NMOG CH4 RAF NMOG/NMHC RATIO			HCHO/NMHC RATIO NMOG+NOX PC+LDT (0- (g/n			3750 LVW) L		NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		NMOG+NOX FLEET STE MDV (10001-14000 GVWR) (g/mi)			
*	*		1.10	0.05		0.086			0.	.101	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance],

California Environmental Protection Agency

**OB Air Resources Board** 

HONDA MOTOR CO., LTD.

Executive Order: A-023-0653-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-023-0653 dated June 13, 2016.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 27 day of October 2016.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

HONDA MOTOR CO., LTD.

Executive Order: A-023-0653-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

# @ Air Resources Board

						A.	TTAC	НМІ	ENT							
	EXH	AUS"	T AND E	VAPO	RATIV	EEMIS	SION S	TAN	DARD	SAND	CERTI	FICATIO	ON L	EVELS		
		EXH	AUST EN	ISSION	STAND	ARDS A	ND CERT	IFICA	TION L	EVELS	(FTP, HW	FET, 50°F	, 20°F	-)		
	FUI	EL TY	mo adj OR	noxide; Nustment f VR [g H0	Ox: oxid actor; 2l c/gallon	des of nit DHS/3DH dispense	rogen; H( HS [g HC/ ed]: on-bo	CHO: test]:	formalde 2/3 days fueling	ehyde; P diurnal- apor red	M: particu +hot-soak; covery; g:	C: non-Cl late matte ; RL [g HC gram; mg: : supplem	r; RAI /mi]: r millig	F: reactive running logical reactive running	rity oss:	
				NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		1	HCHO mg/mi)			PM (g/mi)	
701			C	ERT	STD	CERT	STE		CERT	STD	CER	T STE		CERT	STD	
FTP@5	TP@50K *			*	*	*	*		*	*	*	*	*		*	
GASO		OLIN V3 E	1 (1)	.061	0.125	0.1	2.1		*	*	1	4		*	0.01	
50°F @	4K	*		*	*	*	*		*	*	*	*				
1 3 16 16 16 16 16				FUEL TYPE					NMOG+NO		Ox (g/mi)		CO (g/		mi)	
			POEL TIPE					CERT		STD	C	CERT		STD		
HWFE	T @ 50K				*				,		*			No. 15 bounds	Microsoft all	
HWFET @ UL				GASOLINE-LEV3 E10					0.039		0.125	0.125		A ST		
20°F	@ 50K	C	OLD CO	E10 REG	ULAR G	ASOLIN	E (TIER	.3)			A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		0.7		10.0	
			SF	TP EXHA	USTEN	ISSION	STANDA	RDS	AND C	RTIFIC	ATION LE	EVELS				
V '2-'						US06				SC03			COM	POSITE		
	FUEL 1	YPE		NMOG+		CO (g/mi)	PI (mg/		NMOG (g/i		CO (g/mi)	NMOG+I (g/mi		CO (g/mi)	PM (mg/mi)	
@ 4K	*	*		RT *		*			*		*		\$40 y			
W 411						*					*					
		CE		RT *		*	* *		*		*	0.066		0.6	*	
@ UL GASOLII				D *		*	* *		*		*	0.103		4.2	*	
			BIN									0.10				
		WH	OLE VE	HICLE E								ATION LE	VELS			
					W	HOLE V	EHICLE	EVAP	ORATI	/E TEST	ING		-			
EVAPORATIVE FAMILY		FUEL TYPE		E 3DHS (g/		g/test) @	/test) @ UL		2DHS (g/test)		@ UL				UL	
					RT	STD	TD FEL		RT STD		FEL	- (	CERT		STD	
HHNXR0151VFA		<b>A</b>	ASOLINE A PHASE	HASE 2 0.22 0		0.50			25 0.65				0.00			
(	DRVR / F	UEL	ONLY / C	ANISTE	RBLEE	EVAP	DRATIVE					CERTIFI		ON LEVE	LS	
	EVAPORATIVE		ORVR (g/gallon) @			3			UEL ONLY EVAI DHS RIG TEST		2DHS	RIG TEST	BLEED CANISTE			
FA	MILY	-			Tern	FUE	FUEL TYPE		(g/test) @ UI		-	st) @ UL	_	TEST (g/test) (		
HHNXI	HHNXR0151VFA		SOLINE TIER 2				*		* *		CERT *	STD *	-	*	STD *	

HONDA MOTOR CO.,

Executive Order: A-023-0653-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

@ Air Resources Board

tont applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW: LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

LTD.

## 2017 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE	
ACURA	MDX AWD	PC	3.5	SA9	HHNXR0151VFA	1	P	*	
ACURA	MDX FWD	PC	3.5	SA9	HHNXR0151VFA	1	P	*	
HONDA	PILOT AWD 6AT	PC	3.5	A6	HHNXR0151VFA	1	P	*	
HONDA	PILOT AWD 9AT	PC	3.5	SA9	HHNXR0151VFA	1	P	*	
HONDA	PILOT FWD 6AT	PC	3.5	A6	HHNXR0151VFA	1	P	*	
HONDA	PILOT FWD 9AT	PC	3.5	SA9	HHNXR0151VFA	1	P	*	