California Environmental Protection Agency	HONDA MOTOR CO.,	Executive Order: A-023-0654 New Passenger Cars, Light-Duty Trucks and
Air Resources Board	LTD.	Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST	GROU	P IN	FOR	MATION						
MODEL TEST GROUP VEHICLE CLASS(ES)							FUEL CATEGORY			FUEL TYPE					
2017 HHNXV02.41K3 PC							DEDICATED SINGLE FUEL VEHICLE				GASOLINE				
USEFUL LIFE (miles) VEHICLE EMISSION									N CATEGORY INTERIM / INT			ERN	ERMEDIATE IN-USE STD		
EXH	/ORVR		EVAP		FTP			SF	FTP FTP				SFTP		
15	0000		150000	I	EV3 SULEV3	0 1	EV	3 CC	MPOSITE		PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			EN	ENGINE DISPLACEMENT (L)			
1 WU-TWC, TWC, WR-HO2S, HO2S, DFI									FULL		*				
* *								Р	ARTIAL	AL	L MODELS	2.4			
* *								1	TIAL WITH		*				
			EV	APORATI	/E & REFUEL	.ING (E	EVA	P/OR	VR) FAMIL	Y INF	ORMATION				
EVA	P / ORV	RFAN	MILY	EVAPOR	TIVE STD CA	ATEGO	DRY	,	EVAP EM			SF	PECIA	L FEATURES	
н	HNXR01	21VF7	A		LEV 2				PC *			*			
					EMISSIO	N CRE	DIT		RMATION						
NMOG CREDIT FOR NMOG CREDIT FOR STD FOR W										OPTIONAL EXH. STD FOR WORK TRUCKS					
	*			*	*		-						27		
									N	7101	1	4		N	
r					MOG AND FL	EEI A	AVE	RAGE		TION					
NMOG RAF				375(750 LVW) LDT (MOG+NOX FLEET STD LDT (3751 LVW-8500 3VWR) + MDPV (g/mi)			D NMOG+NOX FLEET STD MDV (10001-14000 GVWR) (g/mi)					
* * 1.10 0.05 0.08				0.05		0.0	086			0	.101			*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of

California Environmental Protection Agency	HONDA MOTOR CO.,	Executive Order: A-023-0654 New Passenger Cars, Light-Duty Trucks and
Ø Air Resources Board	LTD.	Medium-Duty Vehicles
All nesources board		Page 2 of 4

Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of June 2016.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

HONDA MOTOR CO., LTD. Executive Order: A-023-0654 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

														Page	e 3 of 4	
						A	TTAC	HME	NT							
	EXH	AUS	TAND	EVAPO	RATIV	EEMIS	SION	STAN	DARE	S AND	CERT	FICATIO	N LEVE	LS		
		EXH	AUST E	MISSION	STAND	ARDS A	ND CER	TIFICA	TION L	EVELS	(FTP, HW	FET, 50°F,	20°F)			
	FU			onoxide; N justment RVR [g H0	IOx: oxio factor; 21 C/gallon	des of nit DHS/3DH dispense	trogen; H HS [g HC ed]: on-bo	CHO: fo /test]: 2 pard refi	/3 days	ehyde; P s diurnal- vapor rec	M: particu hot-soak	C: non-CH late matter; ; RL [g HC/i gram; mg: i ; suppleme	RAF: reami]: runni milligram	activi ng lo	ty ss;	
	-			NMOG+ (g/m			CO (g/mi)			Ox /mi)		HCHO mg/mi)		PN (g/m		
				CERT	STD	CERT	T ST	DC	ERT	STD	CER	T STD	CER	т	STD	
FTP@50	OK	*		*	*	*	*		*	*	*	*	*		*	
FTP@U		SOLII V3 E		0.020	0.030	0.1	1.	0	*	*	0.4	4	0.00	0.001 0.003		
50°F @4	4K	*		*	*	*	*		*	+	*	*				
				F	JEL TY	DE			N	MOG+NC	Dx (g/mi)		CO (g	/mi)		
						-		CE	RT	STD	CE	RT	:	STD		
HWFET @ 50K				*				*		*	*					
HWFE	T@UL			GASOLINE-LEV3 E10					0.005 0.030							
20°F (@ 50K		GAS	OLINE-C	OLD CO	LOW OC	TANE			-		0	. 6	1	.0.0	
			SF	TP EXH	USTEN	ISSION	STAND	ARDS A	AND C	ERTIFIC	ATION LE	EVELS				
			100			US06				SC03		(COMPOS	ITE		
FUE				NMOG+NOx (g/mi)		CO (g/mi)			ni) NMOG+NO		CO (g/mi)	NMOG+N (g/mi)		O mi)	PM (mg/mi	
RAK	*		CERT	*		*				*	*			-		
@ 4K			STD	*		*	-			*	*					
		CERT *		*	* 2.2			*	*	0.030	0	. 4	*			
@ UL	UL GASOLI		STD	*		*	1	.0		*	*	0.103	4	.2	*	
	1		BIN			ET EL	1.1	-	H			0.050				
		W	HOLE VE	HICLE E	VAPOR	ATIVE E	MISSION	STAN	DARD	SANDO	ERTIFIC	ATION LEV	ELS			
					N	HOLE V	EHICLE	EVAPO	DRATI	VE TEST	ING					
	ORATIV	E	FUEL TY	PE	3DHS (g/test) @	y/test) @ UL			2DHS (g/test) (RL (g/mi) @ U		UL	
				CERT STD		STD	FEL C		Т	STD	FEI	_ C	ERT	ST		
UUNTVDA121VEA I			CA PHAS	1 0	38	0.50	.50 *		37 0.65		*	* 0.		00 0.05		
C	DRVR /	FUEL	ONLY/	CANISTE	R BLEE	DEVAP	ORATIV					CERTIFIC		EVE	LS	
			0010	a la allers)	@ !!!				FUEL ONLY EVAP & CANIST							
	ORATIVE ORVR (g/		R (g/gallon) @ UL		FUE	1 1 1		DHS RIG TEST (g/test) @ UL			RIG TEST st) @ UL			NISTER st) @ 4K		
		F	UEL TYP	E CERT	STD	_			ERT STD		CERT	1	CER	1	STD	
HHNXR	0121VI	TA	ASOLINE TIER 2	0.02	0.20		*	+		*	+	*	*		*	

OB Air Resources Board	LTD.	Medium-Duty Vehicles Page 4 of 4
California Environmental Protection Agency	HONDA MOTOR CO.,	New Passenger Cars, Light-Duty Trucks and
		Executive Order: A-023-0654

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection: DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2017 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS		PZEV TYPE
HONDA	ACCORD	PC	2.4	CV1, SCV7	HHNXR0121VFA	1	P	*