California Environmental Protection Agency

@ Air Resources Board

HONDA MOTOR CO.,

Executive Order: A-023-0666

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| | | | | | TEST GR | OUP IN | FORMAT | ION | - | | | | |
|-------------|------------|--------|-----------------------|-------------------|--|--------|---------|---------------|-------|---|-----------|--|--|
| MODE | - I TI | EST GI | ROUP | VEH | ICLE CLASS(E | ES) | | FUEL CATEGORY | | | FUEL TYPE | | |
| 2017 | нн | NXV02 | .0863 | | PC | 1 | DED | | SIN | GLE FUEL E | GASOLINE | | |
| l | JSEFUL | LIFE | (miles) | V | EHICLE EMIS | SION C | ATEGOR | Y | IN | TERIM / INT | ERMEDIA | TE IN-USE STD | |
| EXH | ORVR | 1 | EVAP | | FTP | | SFTP | | | FTP | | SFTP | |
| 15 | 0000 | | 150000 | LEV | 3 SULEV30 | LEV | 3 СОМРО | SITE | | PM | NMC | G+NOX AND PM | |
| SPE | CIAL FE | ATUR | ES & EXH SYST | | SION CONTRO | DL | | OBD S | TATU | JS | ENGINE | DISPLACEMENT (L) | |
| 1 | | TV | C, WR-H | 02S, H02S, | SFI | | FUI | L | | * | | | |
| * | | | | * . | the second secon | | PART | TIAL | AL | L MODELS | 2.0 | | |
| * | | | | * | | | PARTIA | | | * | | | |
| | | | EV | APORATIVE | & REFUELING | G (EVA | P/ORVR) | FAMILY | INF | ORMATION | | | |
| EVA | P / ORV | RFAN | TILY | EVAPORAT | VE STD CATE | GORY | | AP EMI | | | SPECIA | L FEATURES | |
| Н | HNXR01 | 13VS# | 1 | LEV | 3 OPTION2 | | | F | C | | | * | |
| | | | | | EMISSION O | REDIT | INFORM | ATION | | | | | |
| | A | LLOW | ANCE FO | R TEST GRO | OUP | | NMOG CR | | | NMOG CRI | | OPTIONAL EXH STD FOR WORK | |
| BASE | LINE P | ZEV | AT | PZEV | TZEV | NC | ON-PZEV | ZERO-E | VAP | DO | R | TRUCKS | |
| ALI | MODE | LS | | * | * | | 1 | N N | | | | N | |
| | | | | NM | OG AND FLEE | TAVE | RAGE IN | FORMA | TION | | | | |
| NMOG RAF | CH4 RAF | NMO | FTP G/NMHC ATIO | HCHO/NMH RATIO | PC+LDT | | | LDT | (3751 | X FLEET ST I LVW-8500 MDPV (g/mi) | MDV | NOX FLEET STD (10001-14000 VWR) (g/mi) | |
| * | * | | 1.10 | 0.05 | | 0.086 | | | 0 | .101 | | * | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance],

California Environmental Protection Agency **OB Air Resources Board**

HONDA MOTOR CO., LTD.

Executive Order: A-023-0666 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of September 2016.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

HONDA MOTOR CO., LTD. Executive Order: A-023-0666

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

| EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS | |
|--|--|
| EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) | |

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

| / V = | NMOG+NOx (g/mi) | | | . C | | NC (g/i | | HC (mg | | | M mi) |
|----------|-----------------------|-------|-------|------|-----|------------|-----|-----------|-----|-----------|--------------|
| | | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD |
| FTP@50K | * | * | * | * | * | * | * | * | * | * | * |
| FTP@UL | GASOLINE- LEV3 E10 | 0.018 | 0.030 | 0.0 | 1.0 | * | * | * | 4 | 0.000 | 0.003 |
| 50°F @4K | * | * | * | * | * | * | * | * | * | Politica, | Tany to live |

| 1 125 25 25 | | NMOG+N | Ox (g/mi) | CO (g/mi) | | |
|-------------|--------------------------------------|--------|-----------|-----------|---|--|
| | FUEL TYPE | CERT | STD | CERT | STD | |
| HWFET @ 50K | * | * | * | | Control of the State of the Control | |
| HWFET @ UL | GASOLINE-LEV3 E10 | 0.006 | 0.030 | | | |
| 20°F @ 50K | COLD CO E10 REGULAR GASOLINE (TIER3) | | | 0.4 | 10.0 | |

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

| | | | | US06 | | SC03 | } . | CON | MPOSITE | |
|------|-----------------------|------|--------------------|--------------|---------------|--------------------|--------------|--------------------|-----------------|---------------|
| | FUEL TYPE | 2.4 | NMOG+NOx (g/mi) | CO (g/mi) | PM (mg/mi) | NMOG+NOx (g/mi) | CO (g/mi) | NMOG+NOx (g/mi) | CO (g/mi) | PM (mg/mi) |
| @ 4K | * | CERT | * | * | | * | * | | | |
| | | STD | * | * | | * . | * | | Who says with a | |
| | | CERT | * | * | 1 | * | * | 0.016 | 0.1 | * |
| @ UL | GASOLINE- LEV3 E10 | STD | * | * | 10 | * | * | 0.103 | 4.2 | * |
| | | BIN | | | | | | 0.050 | | |

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

| EVAPORATIVE FAMILY | | | WHOLE \ | /EHICLE | EVAPORA | TIVE TESTIN | IG | | |
|-----------------------|-----------------------|--------------------|---------|---------|---------|---------------|----------------|------|------|
| | FUEL TYPE | 3DHS (g/test) @ UL | | | 2DI | HS (g/test) @ | RL (g/mi) @ UL | | |
| | | CERT | STD | FEL | CERT | STD | FEL | CERT | STD |
| HHNXR0113VSA | GASOLINE- LEV3 E10 | 0.169 | 0.300 | * | 0.202 | 0.300 | * | 0.00 | 0.05 |

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

| | ORVR (g/gallon) @ UL | | | FUEL ONLY EVAP & CANISTER BLEED | | | | | | | | | |
|--------------------|------------------------|------|------|---------------------------------|--------------------------------|-----|--------------------------------|-----|--------------------------------------|-------|--|--|--|
| EVAPORATIVE FAMILY | | | | FUEL TYPE | 3DHS RIG TEST (g/test) @ UL | | 2DHS RIG TEST (g/test) @ UL | | BLEED CANISTER TEST (g/test) @ 4K | | | | |
| | FUEL TYPE | CERT | STD | | CERT | STD | CERT | STD | CERT | STD | | | |
| HHNXR0113VSA | GASOLINE- TIER3 E10 | 0.02 | 0.20 | GASOLINE- LEV3 E10 | * | * | * | * | 0.006 | 0.020 | | | |

California Environmental Protection Agency

@ Air Resources Board

HONDA MOTOR CO.,

Executive Order: A-023-0666

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV: SULEV: super ULEV: ZEV: zero-emission vehicle: PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

| | 2017 MOD | EL YEAR | : VEHI | CLE MODI | ELS INFORI | MAT | ION | |
|-------|-----------|-----------|------------|------------|--------------------|-----|-----|-----------|
| MAKE | MODEL | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE FAMILY | EXH | OBD | PZEV TYPE |
| HONDA | CIVIC 2DR | PC | 2.0 | CV1 | HHNXR0113VSA | 1 | P | PZEV |
| HONDA | CIVIC 4DR | PC | 2.0 | CV1 | HHNXR0113VSA | 1 | P | PZEV |