California	Environmental	Protection	Agency	KIA MO
				000000

O Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UPI	NFC	RMATIO	N						
MODE YEAR	- 1 - 1 -	EST G	ROUP	VEHICLE CLASS(ES)					FU	FUEL CATEGORY			FUEL TYPE			
2017	нк	MXV01	6DBF	PC					DEDICATED SINGLE FUEL VEHICLE			-	GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION							CAT	FEGORY		IN	ITERIM / INT	ERME	DIAT	E IN-USE STD		
EXH	/ORVR		EVAP			FTP		;	SFTP			FTP		SFTP		
12	0000		150000		L	EV2 ULEV			2 SFTP ANDARD			*			*	
SPE	CIAL FE	ATUR		HAUS TEMS		SION CONTRO	L		OI	BD S	ΤΑΤΙ	JS	ENG	INE	DISPLACEMENT (L)	
1	W	U-TWO	C, TWC,	WR-H	02S, 1	HO2S, DFI			FULL		AL	L MODELS	1			
*				*					PARTIA	L		*	1.6			
*				*				P	ARTIAL V FINES			*				
			EV	APOF	RATIVE	& REFUELING	(EV	AP/0	ORVR) FA	MILY	(INF	ORMATION				
EVA	P / ORV	RFAN	MILY	EVAF	PORAT	IVE STD CATE	GOR	Y EVAP EMISSION STD VEHICLE CLASS SPECIAL			L FEATURES					
E	IKMXR01	204BI	5			LEV 2		PC					*			
H	IKMXR01	221AI	<u>.</u>		LEV	3 OPTION1		PC *			*					
F	KMXR01	281BB	E			LEV 2			PC			*				
						EMISSION CI	RED	IT IN	FORMAT	ION						
	А	LLOW	ANCE FO	OR TE	ST GR	OUP		NMOG CREDIT FOR NMOG CREDIT FOR STD				OPTIONAL EXH. STD FOR WORK				
BASE	ELINE PZ	ZEV	AT	PZEV		TZEV	N	NON-PZEV ZERO-EVAP			DC	DOR		TRUCKS		
	*			*		*			N			ľ	1		N	
					NM	OG AND FLEET	T AV	ERA	GE INFO	RMA ⁻	TION	1				
NMOG RAF				PC+LDT (C NMOG+NOX FLEET PC+LDT (0-3750 L (g/mi)		.VW)					MDV	S+NOX FLEET STD IV (10001-14000 GVWR) (g/mi)			
*	*	:	1.04		*	0	.86	0			0	.101			*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

California Environmental Protection Agency

OB Air Resources Board

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of May 2016.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

Om Air Resources Board

KIA MOTORS CORPORATION Executive Order: A-314-0246 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

									·····			
				CO (g/mi)		NOx (g/mi)				(PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
GASOLINE - P@50K TIER 2 UNLEADED		0.022	0.040	0.4	1.7	0.02	0.05	*	8	*	*	
TI	ER 2	0.027	0.055	0.5	2.1	0.02	0.07	*	11	*	0.01	
TI	ER 2	0.044	0.080	0.8	1.7	0.01	0.05	*	16			
All and and				-			NOx (g/	mi)	CO (g/mi)			
			FUEL TYP	E		CE	RT	STD	CERT		STD	
HWFET @ 50K GASOLINE - TIER 2 UNLEADED				0.0	01	0.07			WAT LIKE			
HWFET @ UL GASOLINE - TIER 2 UNLEADED				ED	0.	0.01		San Sant Cal				
20°F@50K GASOLI			COLD CO	LOW OCTA	NE				1.2		10.0	
	TI UNI GASC TI UNI GASC TI UNI 2 50K 2 UL	TIER 2 UNLEADED GASOLINE - TIER 2 UNLEADED GASOLINE - TIER 2 UNLEADED	(g/) CERT GASOLINE - TIER 2 UNLEADED GASOLINE - TIER 2 UNLEADED GASOLINE - TIER 2 0.027 0.027 0.027 0.044 0	GASOLINE - TIER 2 UNLEADED GASOLINE - TIER 2 UNLEADED GASOLINE - TIER 2 UNLEADED GASOLINE - TIER 2 UNLEADED GASOLINE - TIER 2 0.027 0.055 UNLEADED FUEL TYP 50K GASOLINE - TIER 2 UL GASOLINE - TIER 2	(g/mi) (g/mi) CERT STD CERT GASOLINE - TIER 2 0.022 0.040 0.4 UNLEADED 0.027 0.055 0.5 GASOLINE - TIER 2 0.044 0.080 0.8 GASOLINE - TIER 2 0.044 0.080 0.8 GASOLINE - TIER 2 0.044 0.080 0.8 UNLEADED FUEL TYPE 50K GASOLINE - TIER 2 UNLEADED 2 50K GASOLINE - TIER 2 UNLEADED 0.044 0.080 0.8	(g/mi) (g/mi) CERT STD CERT STD GASOLINE - TIER 2 UNLEADED 0.022 0.040 0.4 1.7 GASOLINE - TIER 2 UNLEADED 0.027 0.055 0.5 2.1 GASOLINE - TIER 2 UNLEADED 0.044 0.080 0.8 1.7 GASOLINE - TIER 2 0.044 0.080 0.8 1.7 UNLEADED SOK GASOLINE - TIER 2 UNLEADED UNLEADED GASOLINE - TIER 2 UNLEADED 0.8	(g/mi) (g/mi) (g/mi) (g/mi) CERT STD CERT STD CERT GASOLINE - TIER 2 0.022 0.040 0.4 1.7 0.02 UNLEADED 0.027 0.055 0.5 2.1 0.02 GASOLINE - TIER 2 0.027 0.055 0.5 2.1 0.02 UNLEADED 0.044 0.080 0.8 1.7 0.01 GASOLINE - TIER 2 0.044 0.080 0.8 1.7 0.01 UNLEADED FUEL TYPE 200K GASOLINE - TIER 2 UNLEADED 0.0 201L GASOLINE - TIER 2 UNLEADED 0.0	(g/mi) (g/mi) (g/mi) CERT STD CERT STD CERT STD GASOLINE - TIER 2 UNLEADED 0.022 0.040 0.4 1.7 0.02 0.05 GASOLINE - TIER 2 UNLEADED 0.027 0.055 0.5 2.1 0.02 0.07 GASOLINE - TIER 2 UNLEADED 0.044 0.080 0.8 1.7 0.01 0.05 GASOLINE - TIER 2 UNLEADED 0.044 0.080 0.8 1.7 0.01 0.05 GASOLINE - TIER 2 UNLEADED 0.044 0.080 0.8 1.7 0.01 0.05 FUEL TYPE FUEL TYPE NOx (g/n CERT 0.01 0.01 0.01 OSOK GASOLINE - TIER 2 UNLEADED 0.01 0.01 0.01 0.01	(g/mi) (g/mi) (g/mi) (g/mi) (mg/mi) GASOLINE - TIER 2 UNLEADED 0.022 0.040 0.4 1.7 0.02 0.05 * GASOLINE - TIER 2 UNLEADED 0.027 0.055 0.5 2.1 0.02 0.07 * GASOLINE - TIER 2 UNLEADED 0.027 0.055 0.5 2.1 0.02 0.07 * GASOLINE - TIER 2 UNLEADED 0.044 0.080 0.8 1.7 0.01 0.05 * GASOLINE - TIER 2 0.044 0.080 0.8 1.7 0.01 0.05 * SOK GASOLINE - TIER 2 UNLEADED 0.01 0.07 * 200K GASOLINE - TIER 2 UNLEADED 0.01 0.07 QUL GASOLINE - TIER 2 UNLEADED 0.01 0.09	$\frac{(g/mi)}{CERT} (g/mi)}{(g/mi)} (g/mi) (mg/mi)}$ $\frac{(g/mi)}{CERT} STD CERT STD CERT STD CERT STD \\ GASOLINE - TIER 2 \\ UNLEADED \\ GASOLINE - TIER 2 \\ UNLEADED \\ GASOLINE - TIER 2 \\ UNLEADED \\ \hline D \ O \ O \ O \ O \ O \ O \ O \ O \ O \$	(g/mi) (g/mi) (g/mi) (mg/mi) (

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

States - States	FUEL TYPE		A C B AN THE		US06				3	COMPOSITE			
				NMHC+NOx (g/mi)	CO PM (g/mi) (mg/mi)			NMHC+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	
GASOLINE - TIER 2 @ 4K UNLEADED			CERT	0.04	0.6			0.05	1.0				
0				0.14	8.0			0.20	2.7				
			CERT	*	*		*	*	*	0.057	*	*	
@ UL	GASOLINE - DUL TIER 2 UNLEADED		STD	*	*		*	*	*	0.103	*	*	
			BIN							0.130			
	1	WHO	OLE VE	HICLE EVAPO	RATIVE	MISSION	STAND	ARDS AND	CERTIFIC	ATION LEVELS	5		
					WHOLE \	/EHICLE	EVAPOR	RATIVE TES	TING				
EVAPORATIVE FAMILY FUEL		UEL TYPE 3DH		S (g/test) @ UL			2DHS (g/test) @ UL	RL	UL			
				CERT	STD	FEL	CERT	STD	FE	L CERT		STD	
HKMXI	HKMXR01204BE GASOLIN CA PHAS			10.261	0.50	*	0.31	0.65	*	0.02	0.02 0		
HKMXI	R01221AF		ASOLIN EV3 E1	10 2001	0.350	*	0.230	0.350	*	0.02		0.05	
HEMYRO1281BE		SOLINE	0 24 1	0.50	*	0.40	0.65	*	0.02		0.05		

California Envi	ronmental Prot			KIA MC CORPO	N	Executive Order: A-314-0246 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4						
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS												
FUEL ONLY EVAP & CANISTER BLEED												
EVAPORATIVE FAMILY	ORVR (g/g	gallon) (DUL	FUEL TYPE		IG TEST) @ UL		IG TEST)@UL		ANISTER est) @ 4K		
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
HKMXR01204BE	GASOLINE - TIER 2 UNLEADED	0.06	0.20	*	*	*	*	*	*	*		
HKMXR01221AF	TIER 3 E10 REGULAR GASOLINE (9RVP @ LOW ALT.)	0.03	0.20	GASOLINE- LEV3 E10	0.03	0.0	0.03	0.0	*	*		
HKMXR01281BE	GASOLINE - TIER 2 UNLEADED	0.01	0.20	*	*	* .	*	*	*	*		
LDT<6000#GVWR 8500#ALVW; MDV duty passenger ve emission limit; GV ULEV: ultra LEV; S TZEV: transitional catalyst; NAC: NO NH3OC: ammonia filter for spark-ignit NOXS: NOx senso EGRC: EGR coole fuel injection; DFI// fines on-board diag suffix: series; CNG E10: "10%" ethance continuously varial	INMARUIZOIDE TIER 2 0.01 0.20											

2017 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
HYUNDAI	ACCENT	PC	1.6	M6, SA6	HKMXR01221AF	1	F	*
HYUNDAI	VELOSTER	PC	1.6	AM6,M6	HKMXR01281BE	1	F	*
KIA	RIO	PC	1.6	M6, SA6	HKMXR01204BE	1	F	*
KIA	RIO ECO	PC	1.6	SA6	HKMXR01204BE	1	F	*