California Environmental Protection Agency

⊘ Air Resources Board

KIA MOTORS CORPORATION Executive Order: A-314-0253-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP IN	FORMAT	ION					
MODE	- 1 T	TEST GROUP VEHICL			IICLE CLASS(E	LE CLASS(ES)		FUEL CATEGORY			FUEL TYPE		
2017	HF	HKMXV02.04FF			PC			DEDICATED SINGLE FUEL VEHICLE				GASOLINE	
ı	JSEFUL	LIFE	(miles)	II V	EHICLE EMISS	ION C	ATEGOR	Y	INT	ERIM / INT	ERMEDIA	TE IN-USE STD	
EXH	EXH/ORVR EVAP				FTP	FTP		SFTP		FTP	SFTP		
12	0000		150000	I	EV2 ULEV		EV 2 SF			*	*		
SPE	CIAL FE	ATUR		HAUST EMIS	SION CONTRO	L		OBD ST	ATU	s	ENGINE	DISPLACEMENT (L)	
1		TV	VC, WR-H	O2S, HO2S	, DFI		FUI	LL	ALL				
*	*						PART	PARTIAL *				2.0	
*		* PARTIAL WITH * FINES											
			EV	APORATIVE	& REFUELING	(EVA	P/ORVR)	FAMILY	INFO	DRMATION			
EVA	P / ORV	RFAN	MILY	EVAPORAT	IVE STD CATE	GORY		AP EMIS			SPECIA	L FEATURES	
H	HKMXR01284FE L					EV 2			PC			*	
					EMISSION C	REDIT	INFORM	IATION					
	A	LLOW	ANCE FO	R TEST GR	OUP		MOG CR			NMOG CRE		OPTIONAL EXH.	
BASE	LINE P	ZEV	AT	PZEV	TZEV	NO	N-PZEV	ZERO-E\	/AP	DO	R	TRUCKS	
	* *				*	* N			N			N	
				NM	OG AND FLEE	TAVE	RAGE IN	FORMAT	ION				
NMOG RAF			PC+LDT	NMOG+NOX FLEET S PC+LDT (0-3750 LV (g/mi)		LVW) LDT (3751		NOX FLEET STD NN 751 LVW-8500 + MDPV (g/mi)		OG+NOX FLEET STD MDV (10001-14000 GVWR) (g/mi)			
*	*		1.04	*	(0.086			0.	101		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

@ Air Resources Board

KIA MOTORS CORPORATION Executive Order: A-314-0253-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 2 of 4

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-314-0253 dated May 27, 2016.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

. 1

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

Executive Order: A-314-0253-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

	EXI	HAUST	AND	EVAF	PORATI	/E EMIS	SION S	TANDA	ARD	SAND	CERT	IFICATION	LEVEL	S	
-11, -1		EXH										/FET, 50°F, 2 IC: non-CH4		arbon	
	F	UEL TY	mi ac OI	onoxide ljustme RVR [g	e; NOx: ox ent factor; 2 HC/gallor	ides of nitr 2DHS/3DH dispensed	ogen; HC S [g HC/t d]: on-boa	HO: formest]: 2/3 and refuel	nalde days ling v	ehyde; P diurnal- apor red	M: particu hot-soak covery; g:	ulate matter; I ;; RL [g HC/m gram; mg: m ?: supplemen	RAF: react i]: running illigram; m	ivity loss;	
				NMOG (g/mi)		CO (g/mi)			NOx (g/mi)			HCHO (mg/mi)	1	PM p/mi)	
				CERT	STD	CERT	STD	CEF	RT	STD	CER	T STD	CERT	STD	
FTP@5	OK	ASOLINE TIER 2 UNLEADE	2 (0.017	0.040	0.3	1.7	0.0)2	0.05	*	8	*	*	
FTP@L	JL	ASOLINI TIER 2 UNLEADI	2 (0.022	0.055	0.4	2.1	0.0)2	0.07	*	11	*	0.01	
50°F @	4K	ASOLINI TIER 2 UNLEADI	2 (0.027	0.080	0.2	1.7	0.0	02	0.05	*	16			
					FUEL TY	/DE				NOx (g	g/mi)		CO (g/m	i)	
1 -1 24.	POEL				FOLL 11				CERT		STD	CEF	RT	STD	
HWFE	HWFET @ 50K GASC			SOLINE - TIER 2 UNLEADED				0.01		0.07					
HWFE	T@U	IL	GA:	SOLINE	E - TIER	2 UNLEA	DED	100	0.	02	0.09			245 A	
20°F	20°F @ 50K GASO			OLINE-COLD CO LOW OCTANE				18-3		No.		0.	8	10.0	
			SF	TP EX	HAUST E	MISSION	STANDA	RDS AN	D CI	ERTIFIC	ATION L	EVELS			
177			F 1			US06				SC03	•	C	OMPOSIT	E	
	FUEL	L TYPE		NMHC+NOx (g/mi)		CO (g/mi)	PN (mg/r		NMHC+No (g/mi)		CO (g/mi)	NMOG+NO (g/mi)			
@ 4K	GASOLINE TIER 2		ER 2		.02	0.7			0.04		0.1				
0			STD	0	.14	8.0			0.	20	2.7		The state		
			CERT		*	*	*		1		*	0.048	*	*	
@ UL	TI	LINE - ER 2 EADED	STD	D *		*	* *		*		*	0.103	*	*	
			BIN			17		THE WE	- 7	4,732		0.130	es i e		
		WH	OLE VE	HICLE	EVAPOR	RATIVE EN	IISSION	STANDA	RDS	S AND C	ERTIFIC	ATION LEVE	LS		
				WHOLE VEHICLE EVAP				ATI\	/E TEST	ING					
EVAP	ORAT		UEL TY	TYPE 3DHS (g		(g/test) @	g/test) @ UL		2DHS (g/test)		@ UL	F	RL (g/mi)	@ UL	
	I				CERT	STD	FEL	CERT	RT STD		FE	L CE	RT	STD	
HKMXF	0128	AFE	ASOLIN A PHAS		0.35	0.50	*	0.22		0.65	*	0.	01	0.05	

KIA MOTORS CORPORATION Executive Order: A-314-0253-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

				FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
HKMXR01284FE	GASOLINE - TIER 2 UNLEADED	0.00	0.20	•	*	*	*	*	*	*		

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV; heavy-duty vehicle; ECS; emission control system; CERT; certification; STD; standard; FEL; family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler, AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85; "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission, SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2017 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
KIA	FORTE	PC	2.0	M6,SA6	HKMXR01284FE	1	F	*
KIA	FORTE KOUP	PC	2.0	M6,SA6	HKMXR01284FE	1	F	*
KIA	FORTE5	PC	2.0	M6,SA6	HKMXR01284FE	1	F	*