California Environmental Protection Agency

OB Air Resources Board

MITSUBISHI MOTORS CORPORATION

Executive Order: A-086-0359

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GROU	JP INI	FORMATIC	N					
MODE		EST G	ROUP	VEH	VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
2017	нм	TXV02	. 4G9X		PĊ ,	1	DEDICATED SINGLE FUE			GASOLINE			
- (JSEFUL	LIFE	(miles)	V	EHICLE EMISSI	ON C	ATEGORY	1	NTERIM / INT	ERMEDIA	TE IN-USE STD		
EXH	/ORVR		EVAP		FTP	SFTP	SFTP FTP		SFTP				
12	0000		150000	I	EV2 LEV	LEV 2 SFTI STANDARD			*	*			
SPE	CIAL FE	ATUR		AUST EMIS	SION CONTROL		O	BD STAT	us	ENGINE	DISPLACEMENT (L)		
1	TWC, WR-HO2S, HO2S, SFI, EGR FULL								LL MODELS				
*				*			PARTIA	PARTIAL *			2.0, 2.4		
*				*			PARTIAL I		*				
			EV	APORATIVE	& REFUELING	(EVA	P/ORVR) F	AMILY IN	FORMATION				
EVA	P / ORV	R FAN	MILY	EVAPORAT	VE STD CATEG	ORY		P EMISSI		SPECIA	L FEATURES		
E	MTXR01	35A1I			LEV 2	LEV 2				*			
					EMISSION CR	EDIT	INFORMA	TION					
	A	LLOW	ANCE FO	R TEST GRO	DUP		MOG CRE		NMOG CRI		OPTIONAL EXH STD FOR WORK		
BASE	ELINE P	ZEV	АТ	PZEV	TZEV	NO	N-PZEV ZE	RO-EVA	P DO	R	TRUCKS		
	*			*	*	* N			N		N		
				NM	OG AND FLEET	AVE	RAGE INFO	RMATIO	N				
NMOG RAF	NIMO (C/NIMIH)			PAHO:			LVW)	NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)					
*	*		1.04	*	0.	.086			*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of

California Environmental Protection Agency

⊘ Air Resources Board

MITSUBISHI MOTORS CORPORATION

Executive Order: A-086-0359 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of June 2016.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

GASOLINE -

TIER 2

UNLEADED

0.024 0.20

HMTXR0135A1D

MITSUBISHI MOTORS CORPORATION

Executive Order: A-086-0359

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

								A	ITAC	HIVII	ENI						
	EX	HAU	JST	ANI) EV	/APOF	RATIVE	EMIS	SION S	STAN	DAR	S AND	CERTI	FIC	NOITA	LEVELS	3
		E	XHA	UST	EMIS	SION S	TANDA	RDS A	ND CERT	TIFICA	TION L	EVELS (FTP, HW	FET,	50°F, 20	°F)	
FUEL TYPE					mono adjus ORV	oxide; No stment fa R [g HC	Ox: oxid actor, 2D /gallon o	es of nite HS/3DH dispense	rogen; Ho HS [g HC/ ed]: on-bo	CHO: /test]: ard re	formald 2/3 days fueling	ehyde; Pl s diurnal- vapor rec	oon; NMH M: particu hot-soak; covery; g: ure; SFTP	late n RL [gram	natter; R/g HC/mi]: ; mg: mill	AF: reactive running I	vity oss;
		. 11			NMOG (g/mi)			CO (g/mi)		NOx (g/mi)		HCH (mg/n				M mi)	
					CE		STD	CERT			CERT	STD	CER		STD	CERT	STD
FTP@5	OKI	GASOLINE - CA PHASE 2			0.0	350 (0.075	0.50	3.4	1	0.024	0.05	*		15 *		*
FTP@l		CASOLINE -			0.0	421 (0.090	0.64	4.2	2 (0.036	0.07	*		18	*	0.01
50°F @		GASOL CA PH			0.0	666	.150	0.65	3.4	4	0.016	0.05	*		30		
40.						EII	EI TVD	=				NOx (g	J/mi)			CO (g/mi)
1. 12 m - 3 - 1					FUEL TYPE					CE	RT	STD		CERT		STD	
HWFE	Т@5	50K			GASOLINE - CA PHASE 2					0.	012	2 0.07				i m	
HWFE	T@	UL			GA	SOLINE	- CA	PHASE	2		0.	024	0.09		10%		
20°F @ 50K GASOLINE-COLD CO H						HIGH OCTANE						2.06		10.0			
					SFTF	EXHA	JST EM	ISSION	STANDA	ARDS	AND C	ERTIFIC	ATION LE	VEL	S		
								US06			SC03				COMPOSITE		
	FUE	UEL TYP		(PE		NMHC+NOx (g/mi)		CO PM (g/mi) (mg/				C+NOx mi)	CO (g/mi)	NMOG+NO (g/mi)		CO (g/mi)	PM (mg/mi)
GASOL @ 4K CA PH		OLINE PHASE			Т	0.02	3	0.71	-		0.014		0.54				
				STE		0.14		8.0			0.	20	2.7			-	
		ASOLINE - S		CERT		*		*		t	*		*	0.059		*	*
@ UL				STE		*		*	*	•		*	*	C	.103	*	*
				BIN					1/ 7/	77940	100		-	C	.100		1 -
			WH	OLE '	VEHI	CLE EV	APORA	TIVE E	MISSION	STAI	NDARD	SANDC	ERTIFIC	OITA	N LEVEL	S	
							W	HOLE V	EHICLE	EVAP	ORATI	VE TEST	ING				
EVAPORATIVE FAMILY		FUEL TYPE			3DHS (g/test				2DHS (g/test)				RL (g/mi) @ U				
			GASOLINE -			CERT S		FEL	CE			FEL		CER	-	STD	
HMTXR0135A1D			CA PHASE 2			2			.50 *		.40	0.65	*		0.012		0.05
(ORVE	R / FUI	EL C	ONLY	/CA	NISTER	BLEE	EVAPO	ORATIVE				RDS AND				ELS
				051/-			2 111	-					P & CANI				41110
EVAP	ORA AMIL		ORVR (g/ga			jalion) (JUL UL	FUE	FUEL TYPE		3DHS RIG TES (g/test) @ UL		2DHS RIG (g/test) @				
			FU	FUEL TYPE C			STD			CE	RT .	STD	CERT		STD	CERT	STD
			103	TOT TO	777			1					1	1			4

@ Air Resources Board

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR; gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ŽEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler, AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2017 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE	
MITSUBISHI MOTORS	LANCER	PC	2.0	scv6	HMTXR0135A1D	1	F	*	
MITSUBISHI MOTORS	LANCER	PC	2.4	scv6	HMTXR0135A1D	1	F'	*	
MITSUBISHI MOTORS	LANCER SPORTBACK	PC	2.0	scv6	HMTXR0135A1D	1	F	* =	