California Environmental Protection Agency

⊘ Air Resources Board

FUJI HEAVY INDUSTRIES, LTD.

Executive Order: A-002-0217

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GRO	UP I	NF	ORMAT	ION						
MODE		TEST C	ROUP	V	VEHICLE CLASS(ES)					FUEL CATEGORY				FUEL TYPE		
201	7 Н	FJXV0	2.0AJM	PC					DEDICATED SINGLE FUE				GASOLINE			
USEFUL LIFE (miles)					VEHICLE EMISSION CATEGOR				TEGOR	Y	TERIM / IN	TERM	ERMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP				SFTP			FTP			SFTP		
150000 15000		150000	11	LEV2 LEV OPTION CERTIFYING TO LEV3 LEV NMOG+NOX			LEV 2 SFTP STANDARD			*			*			
SPECIAL FEATURES & EXHAUST EMISSION CONTRO SYSTEMS										OBD STATUS			ENGINE DISPLACEMENT (L)			
1		TWC (2), WR-HC	O2S, HO2S, SFI, DFI					FUL	L	ALL MODELS					
*	*								PART	PARTIAL *			2.0			
*	* *								PARTIAI	*						
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION															
EVA	AP / OR	VR FA	MILY	EVAPOR	PORATIVE STD CATEGOR					EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	1223A	.U		LEV 2					E	°C		*				
					1	EMISSION CF	REDI	T II	NFORM	ATION						
	ALLOWANCE FOR TEST GROUP											EDIT FOR STD FO		OPTIONAL EXH. STD FOR WORK		
BAS	ELINE F	PZEV	АТ	PZEV				ON	I-PZEV Z	ZERO-EVAP		P DOR			TRUCKS	
* *					*				N .			и и				
NMOG AND FLEET AVERAGE INFORMATION																
NMOG RAF	I KINACC/KINALC I			HCHO/N RATI		NMOG+NOX FL PC+LDT (0-37 (g/mi)				NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi						
*	*		1.04	0.026 0.086						0.101				*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

California Environmental Protection Agency

Om Air Resources Board

FUJI HEAVY INDUSTRIES, LTD.

Executive Order: A-002-0217

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of May 20

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

FUJI HEAVY INDUSTRIES, LTD.

Executive Order: A-002-0217 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

OB Air Resources Board

								A	TTAC	HM	ENT						
	E			-	- Charles and Committee	-	-				-		D CERT	-	-	-	S
		E	XH	AUST E	MISS	ION S	TANDA	ARDS A	ND CER	RTIFIC	ATION	LEVELS	(FTP, HV	VFET,	50°F, 20	°F)	
		FUEL TYPE			onoxi ljustm RVR	de; No nent fa [g HC.	Ox: oxid octor; 2E gallon o	les of ni DHS/3D dispense	trogen; h HS [g H(ed]: on-b	HCHO: C/test]: loard re	formalo 2/3 day efueling	dehyde; f ys diurna vapor re	rbon; NMI PM: partic I+hot-soak covery; g: dure; SFTI	ulate i ; RL gram	matter; R. [g HC/mi] n; mg: mil	AF: reacti : running ligram; m	vity loss;
					NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		HCH(-	M mi)
					CERT		STD	CERT	T ST	D	CERT STD				STD	CERT	STD
FTP@5	OK		*		*		*	*	*		*	*	*	*		*	*
FTP@l		GASOI CA PI		1 (.051	.3 (.160	1.25	4.	2	*	*	0.8	3	18	0.000	0.01
50°F @			OLINE - PHASE 2		.055	0 0	.320	0.75	4.	2	*	*	0.5		30		
					FUEL TYPE				NMOG+NOx		x (g/mi)			CO (g/m)		
					PUELTIPE			_	<u> </u>		CI	ERT	STD	CE		Г	STD
HWFE	T @	50K					*					*	*				
HWFET @ UL					GASOLINE - CA PHASE 2					0.	0.0440		0.160				
20°F @ 50K G				GAS	ASOLINE-COLD CO HIGH OCTANE					1 4 1				1.90		10.0	
				S	TP E	XHAL	JST EM	ISSION	STAND	ARDS	AND C	ERTIFIC	ATION L	EVEL	.s		
		US06								SC03			COMPOSITE				
	FUEL TY		PE	,,		NMHC+NOx (g/mi)				M g/mi)		C+NOx /mi)	CO (g/mi)	NMOG+NO (g/mi)		CO (g/mi)	PM (mg/mi)
0.414	GAS			CERT	T 0.083		5.07			0.037		0.57	0.57		11.1		
@ 4K	CA			STD		0.14		8.0	0		0	.20	2.7				
		CEF			T *			*		*		*		0	.0707	*	*
@ UL		SOLINE - ST			D *			•		*		*	*	().103	*	*
	CA	BIN		BIN	1		±1							0.110			
			WH	OLE VI	HICL	EEV	APORA	TIVE	MISSIO	N STA	NDARD	S AND	CERTIFIC	ATIO	N LEVEL	S	
EVAP	ORA	TIVE								EVAF	PORATI	VE TES	TING		RI	. (g/mi) @	D UL
	MIL		F	UEL TY	PE			/test) @ UL			2DHS (g/test)						
			CZ	COT TATE			STD FEL		CE	RT	STD	FE	<u> </u>	CER	Т	STD	
			PHASE	SE 2 0.397 0					0.65		*			0.000 0.05			
(ORVE	R / FU	EL C	ONLY /	CANIS	STER	BLEED	EVAP	ORATIV				RDS AND				ELS
EVAPORATIVE FAMILY				ORVR (R (g/gallon) @ UL			3		30	OHS RIG TEST g/test) @ UL		2DHS RIG 1 (g/test) @		TEST BLEED CANIS		
			FU	EL TYP	EC	ERT	STD	1		CE	ERT STD		CERT			CERT	STD
HFJXR01223AU		23AU	7	SOLINE TIER 2 VLEADE	NE - 2 0.009 0.20		0.20	*			* *		*		*	*	*

California Environmental Protection Agency

OB Air Resources Board

FUJI HEAVY INDUSTRIES, LTD. Executive Order: A-002-0217

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for sparkignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS; PM sensor; RDQS; reductant quality sensor; NH3S; ammonia sensor; EGR; exhaust gas recirculation; EGRC; EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85; "85%" ethanol ("15%"gasoline) fuel; E10; "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

	2017 MODEL YEAR: VEHICLE MODELS INFORMATION												
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE					
SUBARU	BRZ	PC	2.0	M6,SA6	HFJXR01223AU	1	F	* '					
TOYOTA	86	PC	2.0	M6,SA6	HFJXR01223AU	1	F	*					