## California Environmental Protection Agency

**⊘** Air Resources Board

TOYOTA MOTOR CORPORATION

Executive Order: A-014-0928

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

						TEST GROU	IP INFOR	RMATION	1				
MODE		TEST GROUP			VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE		
2017	7 нт	HTYXV03.5B6C			PC			DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
USEFUL LIFE (miles)					VEHICLE EMISSION CATEGO				RY INTERIM / INTERMEDIATE IN-USE				
EXH/ORVR			EVAP		FTP		SFTP			FTP		SFTP	
12	120000 1500		150000		LEV	LEV2 ULEV		EV 2 SFTP STANDARD		*.		*	
(NRI) STATILIS									DISPLACEMENT (L)				
1	SFI, 2WR-HO2S, 2TWC, 2HO2S, TWC FULL *												
*	* PARTIAL ALL MODELS 3.5								3.5				
*	* PARTIAL WITH * FINES												
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EVAP / ORVR FAMILY EVAI				EVAPOR	PORATIVE STD CATEGORY			EVAP EMISSION STD VEHICLE CLASS			SPECIA	SPECIAL FEATURES	
]	HTYXR0115A12				LEV 2				PC			HCT	
				4		EMISSION CR	EDIT INF	ORMATI	ON				
ALLOWANCE FOR TEST GROUP							NMOG CREDIT FOR NMOG CR				OPTIONAL EXH. STD FOR WORK		
BASELINE PZEV AT			PZEV TZEV			NON-PZEV ZERO-EVAP DO			R TRUCKS				
	*			*		*	N		N I		ſ	N	
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO				NMOG+NOX PC+LDT (0- (g/i	3750 LV	750 LVW) LD1		MOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10001-14000 GVWR) (g/mi)	
*	*		1.04	0.0	18	0.086 0.101				*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of

TOYOTA MOTOR CORPORATION

Executive Order: A-014-0928 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of May 2016.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

GASOLINE

TIER 2

UNLEADED

0.040

0.20

HTYXR0115A12

TOYOTA MOTOR CORPORATION

Executive Order: A-014-0928

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

+

## ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP **FUEL TYPE** NMOG CO NOx HCHO PM (g/mi) (g/mi) (g/mi) (mg/mi) (g/mi) CERT STD CERT STD CERT STD CERT STD CERT STD GASOLINE -0.05 FTP@50K 0.0167 0.040 0.21 1.7 0.019 8 CA PHASE 2 GASOLINE -0.021 0.07 FTP@UL 0.0181 0.055 0.23 2.1 11 0.01 CA PHASE 2 50°F @4K NOx (g/mi) CO (g/mi) **FUEL TYPE** CERT STD CERT STD GASOLINE - CA PHASE 2 0.017 0.07 HWFET @ 50K HWFET @ UL GASOLINE - CA PHASE 2 0.019 0.09 GASOLINE-COLD CO HIGH OCTANE 0.56 20°F @ 50K 10.0 SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS US06 COMPOSITE SC03 NMHC+NOx **FUEL TYPE** CO PM NMHC+NO<sub>X</sub> CO NMOG+NO<sub>x</sub> CO PM (g/mi) (g/mi) (mg/mi) (g/mi) (g/mi) (g/mi) (g/mi) (mg/mi) 0.61 0.033 0.04 GASOLINE -CERT 0.027 CA PHASE 2 @ 4K STD 8.0 0.20 2.7 0.14 CERT \* \* \* \* 0.0371 \* \* GASOLINE -0.103 \* STD @ UL CA PHASE 2 WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS WHOLE VEHICLE EVAPORATIVE TESTING RL (g/mi) @ UL **EVAPORATIVE FUEL TYPE** 3DHS (g/test) @ UL 2DHS (g/test) @ UL FAMILY FEL CERT STD FEL CERT STD CERT STD GASOLINE -0.005 0.05 HTYXR0115A12 TIER 2 0.158 0.50 0.65 UNLEADED ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS **FUEL ONLY EVAP & CANISTER BLEED** ORVR (g/gallon) @ UL **3DHS RIG TEST** 2DHS RIG TEST **BLEED CANISTER EVAPORATIVE** (g/test) @ UL (g/test) @ UL TEST (g/test) @ 4K FAMILY **FUEL TYPE** CERT CERT CERT STD CERT STD STD STD FUEL TYPE

+

\*

TOYOTA MOTOR CORPORATION

Executive Order: A-014-0928

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV; heavy-duty vehicle; ECS; emission control system; CERT; certification; STD; standard; FEL; family emission limit; GWWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2017 MODEL YEAR: VEHICLE MODELS INFORMATION											
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYRE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE			
LEXUS	ES 350	PC	3.5	SA6	HTYXR0115A12	1	P	*			
TOYOTA	CAMRY	PC	3.5	SA6	HTYXR0115A12	1	P	*			