California Environmental Protection Agency

OB Air Resources Board

FORD MOTOR COMPANY

Executive Order: A-010-2049

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP IN	FORMAT	ION					
MODE		EST G	ROUP	VEH	IICLE CLASS(ES)		FUEL C	ATE	GORY	FUEL TYPE		
2018	JF	MXV02	.ovzQ		PC		E	PLUG-I			G	ASOLINE	
- (JSEFUL	LIFE	(miles)	1	EHICLE EMIS	SION C	ATEGOR	Y	IN'	TERIM / INT	ERMEDIA	TE IN-USE STD	
EXH	ORVR		EVAP		FTP		SFTP			FTP		SFTP	
15	0000		150000	LE	V3 SULEV30	LEV	3 СОМРО	SITE		PM		PM	
SPE	CIAL FE	ATUR		HAUST EMIS	SION CONTRO	DL		OBD ST	ΓΑΤU	S	ENGINE	DISPLACEMENT (L)	
1	ı	WC (2)	, HO2S,	SFI, WR-	HO2S, EGR		FUI	LL		*			
*				*			PART	ΓIAL	ALI	MODELS	2.0		
*				*	V.		PARTIA		-	*			
			EV	APORATIVE	& REFUELING	G (EVA	P/ORVR)	FAMILY	INF	ORMATION		***************************************	
EVA	P / ORV	R FAN	MILY	EVAPORAT	IVE STD CATE	GORY		AP EMIS			SPECIA	L FEATURES	
J	FMXR01	45HCE	5	LEV 3 O	PTION2 WITH	FEL		P	C			нст	
					EMISSION C	REDIT	INFORM	IATION					
	. A	LLOW	ANCE FO	R TEST GR	OUP		NMOG CR			NMOG CR		OPTIONAL EXH STD FOR WORK	
BASE	LINE P	ZEV	AT	PZEV	TZEV	NC	N-PZEV	ZERO-E	VAP	DC	R	TRUCKS	
	*			*	ALL MODEL	S	1	N		N		N	
				NM	OG AND FLEE	TAVE	RAGE IN	FORMA	ΓΙΟΝ				
NMOG RAF	CH4 RAF	NMO	FTP G/NMHC ATIO	HCHO/NMI RATIO	PC+LD1			LDT	3751	(FLEET ST LVW-8500 (IDPV (g/mi)	MDV	NOX FLEET STD (10,001-14,000 VWR) (g/mi)	
*	*	:	1.10	*		0.079			0.	092		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

California Environmental Protection Agency

⊘ Air Resources Board

FORD MOTOR COMPANY

Executive Order: A-010-2049

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

For evaporative family JFMXR0145HCE, the manufacturer has attested to compliance with the 0.02 inch effective leak diameter standard in 13 CCR Section 1976(b)(1)(G)6 ["Effective Leak Diameter Standard And Procedure"].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

FORD MOTOR COMPANY

Executive Order: A-010-2049

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION	LEVELS
ENITION AND EARL STORT ELITISCICIT STATES AND SERVING TO THE	

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)
CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity
adjustment factor: 2DHS/3DHS [g HC/test]: 2/3 days djurnal+hot-soak: RL [g HC/mi]: running loss:

ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG+NOx (g/mi)			CO NOx HCHO (g/mi) (mg/mi)						M mi)
0		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- LEV3 E10	0.026	0.030	0.2	1.0	*	*	*	4	*	0.003
50°F @4K	*	*	*	. *	*	*	*	*	*	4	

	FUEL TYPE	NMOG+N	IOx (g/mi)	CO (g/mi)		
	POEL TIPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	* .		1	
HWFET @ UL	GASOLINE-LEV3 E10	0.027	0.030			
20°F @ 50K	GASOLINE - COLD CO LOW OCTANE EPA TIER 3 E10			0.4	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

-				US06	4	SC03	3	COM	POSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			1 = 1 = =
@ 41.		STD	*	*	2 4 2 1	*	*			
		CERT	*	*	*	*	*	0.015	0.3	*
@ UL	GASOLINE- LEV3 E10	STD	*	*	10	*	*	0.097	4.2	*
		BIN		,				0.040		3

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE VEHICLE EVAPORATIVE TESTING	NG					
EVAPORATIVE FAMILY	FUEL TYPE	3DH	S (g/test)	@ UL	2D	HS (g/test) (@ UL	RL (g/n	ni) @ UL
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
JFMXR0145HCE	GASOLINE- LEV3 E10	0.175	0.300	0.300	*	0.300	0.300	0.00	. 0.05

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

					FUEL C	NLY EVA	P & CANIS	TER BLE	ED	
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K	
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD
JFMXR0145HCE	EPA TIER3 E10 TEST FUEL		0.20	*	*	*	*	*	*	*

California Environmental Protection Agency

⊘ Air Resources Board

FORD MOTOR COMPANY

Executive Order: A-010-2049

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: _DT<6000#GVWR,3751-5750#LVW: LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR; gross vehicle weight rating; LVW: loaded vehicle weight; ALVW; adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic: DOR; direct ozone reducing; HCT; hydrocarbon trap; BCAN; bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semiautomatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2018 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
FORD	FUSION ENERGI PLUG-IN HYBRID FWD	PC	2.0	CV1	JFMXR0145HCE	1	P	TZEV