

## Table of Contents

Method 1 - Sample and Velocity Traverses

Method 2 - Velocity and Volumetric Flow Rate

Method 2A - Gas Volume Through Pipes and Small Ducts

Method 3 - Gas Analysis

Method 4 - Moisture Content

Method 5 - Particulate Matter Emissions

Method 5A - Particulate Matter Emissions (Asphalt Processing and Roofing Sources)

Method 5E - Particulate Matter Emissions (Wool Fiberglass)

Method 6 - Sulfur Dioxide

Method 7 - Nitrogen Oxides

Method 8 - Sulfuric Acid Mist and Sulfur Dioxide

Method 10 - Carbon Monoxide

Method 11 - Hydrogen Sulfide

Method 15 - Sulfides

Method 16 - Sulfur

Method 16A - Total Reduced Sulfur Emissions

Method 17 - Particulate Matter Emission (In-Stack)

Method 20 - Gas Turbines

Method 21 - Volatile Organic Compound Leaks

Method 100 - Continuous Sampling

Method 150 - Hydrocarbon Emissions (Fixed Roof Tanks)

Method 501 - Determination of Size Distribution of Particulate Matter Emissions from Stationary Sources

The test methods in this volume are incorporated by references in Article 2, Subchapter 8, Chapter 1, Part III, Title 17 California Code of Regulations as follows:

Article 2. Test Methods for Determining Compliance with District Nonvehicular Emission Standards.

94100. Applicability

The test methods set forth in this article shall be used to determine compliance with the nonvehicular emission standards of the districts. However, where a district board, air pollution control officer or executive officer has established a test method concerning the same subject as a test method set forth in this article, the district test method shall be used to determine compliance with the district's nonvehicular emission standards.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94101. Method 1 - Sample and Velocity Traverses.

The test procedure for determining traverse points for sample and velocity measurements is set forth in the Air Resources Board's Method 1, Sample and Velocity Traverses for Stationary Sources, adopted June 29, 1983, as amended March 28, 1986.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94102. Method 2 - Velocity and Volumetric Flow Rate.

The test method for determining stack gas velocity and volumetric flow rate using a type S pitot tube is set forth in the Air Resources Board's Method 2, Determination of Stack Gas Velocity and Volumetric Flow Rate (Type S Pitot Tube), adopted June 29, 1983.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94117. Method 2A - Gas Volume Through Pipes and Small Ducts.

The test method for determining gas flow rates in pipes and small ducts is set forth in the Air Resources Board's Method 2A, Direct Measurement of Gas Volumes Through Pipes and Ducts, adopted March 28, 1986.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94103. Method 3 - Gas Analysis.

The test method for determining carbon dioxide, oxygen, excess air and molecular weight on a dry basis in stack gases is set forth in the Air Resources Board's Method 3, Gas Analysis for Carbon Dioxide, Oxygen, Excess Air, and Dry Molecular Weight, adopted June 29, 1983, as amended March 28, 1986.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94104. Method 4 - Moisture Content.

The test method for determining the moisture content in stack gases is set forth in the Air Resources Board's Method 4, Determination of Moisture Content in Stack gases, adopted June 29, 1983.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94105. Method 5 - Particulate Matter Emissions.

The test method for determining particulate matter emissions is set forth in the Air Resources Board's Method 5, Determination of Particulate Matter Emissions from Stationary Sources, adopted June 29, 1983, as last amended July 28, 1997, which is incorporated herein by reference.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, 39666 and 40001, Health and Safety Code.

94118. Method 5A - Particulate Matter Emissions (Asphalt Processing and Roofing Sources).

The test method for determining particulate emissions from asphalt roofing industry sources is set forth in the Air Resources Board's Method 5A, Determination of Particulate Emissions from the Asphalt Processing and asphalt Roofing Industry, adopted March 28, 1986.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94119. Method 5E - Particulate Matter Emissions (Wool Fiberglass).

The test method for determining wool fiberglass particulate emissions is set forth in the Air Resources Board's Method 5E, Determination of Particulate Emissions from the Wool Fiberglass Insulation Manufacturing Industry, Adopted March 28, 1986.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94106. Method 6 - Sulfur Dioxide.

The test method for determining sulfur dioxide emissions is set forth in the Air Resources Board's Method 6, Determination of Sulfur Dioxide Emissions from Stationary Sources, adopted June 29, 1983.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94107. Method 7 - Nitrogen Oxides.

The test method for determining nitrogen oxide emissions is set forth in the Air Resources Board's Method 7, Determination of Nitrogen Oxide Emissions from Stationary Sources, adopted June 29, 1983, as last amended July 28, 1997, which is incorporated herein by reference.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, 39666 and 40001, Health and Safety Code.

94108. Method 8 - Sulfuric Acid Mist and Sulfur Dioxide.

The test method for determining sulfuric acid mist and sulfur dioxide emissions is set forth in the Air Resources Board's Method 8, Determination of Sulfuric Acid Mist and Sulfur Dioxide Emissions from Stationary Sources, adopted June 29, 1983.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94109. Method 10 - Carbon Monoxide.

The test method for determining carbon monoxide emissions is set forth in the Air Resources Board's Method 10, Determination of Carbon Monoxide Emissions from Stationary Sources, adopted June 29, 1983.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94110. Method 11 - Hydrogen Sulfide.

The test method for determining the hydrogen sulfide content in petroleum refinery fuel gas streams is set forth in the Air Resources Board's Method 11, Determination of Hydrogen Sulfide Content of Fuel Gas Streams in Petroleum Refineries, adopted June 29, 1983.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94111. Method 15 - Sulfides.

The test method for determining hydrogen sulfide, carbonyl sulfide, and carbon disulfide emissions is set forth in the Air Resources Board's Method 15, Determination of Hydrogen Sulfide, Carbonyl Sulfide, and Carbon Disulfide Emissions from Stationary Sources, adopted June 29, 1983.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94112. Method 16 - Sulfur.

The test method for determining emissions of total reduced sulfur is set forth in the Air Resources Board's Method 16, Semicontinuous Determination of Sulfur Emissions from Stationary Sources, adopted June 29, 1983.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94137. Method 16A - Total Reduced Sulfur Emissions.

The test method for determining total reduced sulfur emissions is set forth in the Air Resources Board's Method 16A, Determination of Total Reduced Sulfur Emissions from Stationary Source (Impinger Technique), adopted March 18, 1987, which is incorporated herein by reference.

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

Method 17 - Particulate Matter Emission (In-Stack).

set forth in the Air Resources Board's Method 17, Determination of Particulate Matter Emissions from Stationary Sources (In-stack Filtration Method), adopted June 29, 1983.

Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

Method 20 - Gas Turbines.

The test method for determining emissions from stationary gas turbines is set forth in the Air Emissions from Stationary Gas Turbines, adopted March 28, 1986.

NOTE:

Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94124. \_\_\_\_\_

The test method for determining volatile organic compound leaks from process equipment is set forth in the Air Resources Board's Method 21, Determination of Volatile Organic Compound Leaks,

NOTE: Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference:

94114. Method 100 - Continuous Sampling.

Board's Method 100, Procedures for Continuous Gaseous Emission Stack Sampling, adopted June 29, 1983, as last amended July 28, 1997, which is incorporated herein by reference.

Authority cited: Sections 39600, 39601, and 39607, Health and Safety Code. Reference: Sections 39515, 39516, 39605, 39607, 39666 and 40001, Health and Safety Code.

Method 150 - Hydrocarbon Emissions (Fixed Roof Tanks).

The test method for determining hydrocarbon emissions from fixed-roof crude oil process tanks is Fixed-Roof Crude Oil Process Tanks, adopted March 28, 1986.

NOTE:

Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.

94140, \_\_\_\_\_  
Stationary Sources.

The test procedure for determining particle size distribution is set forth in the Air Resources Stationary Sources, adopted March 23, 1988, as last amended September 12, 1990.

NOTE:

Sections 39515, 39516, 39605, 39607, and 40001, Health and Safety Code.