

## **Modification Highlights for Executive Orders VR-201-Q and VR-202-Q**

NOTE: Global change for Executive Orders and Installation, Operation, and Maintenance Manuals; changed reference from “Healy Phase II Enhanced Vapor Recovery (EVR) System” to “Assist Phase II Enhanced Vapor Recovery (EVR) System”.

### **Part I: Executive Order**

#### Legal Language:

- Added “whereas” paragraph describing the nature of the amendment request from Veeder-Root to add a Catlow re-connectable breakaway;
- Added “whereas” paragraph describing the nature of the amendment request from Vapor Systems Technologies (VST) to add a VST re-connectable breakaway;
- Added “whereas” paragraph describing the nature of the amendment request from Veyance Technologies Incorporated (Goodyear) to add the Goodyear low permeation hose assembly;
- Added “whereas” paragraph describing the nature of the amendment request from the owner of the Sherman Way Chevron to add a below-grade vaulted tank configuration;
- Added “whereas” paragraph changing the title of Executive Order VR-201 from “Healy Phase II Enhanced Vapor Recovery (EVR) System Not Including In-Station Diagnostic (ISD) System” to “Assist Phase II Enhanced Vapor Recovery (EVR) System not including In-Station Diagnostics (ISD)” and changing the title of Executive Order VR-202 from “Healy Phase II Enhanced Vapor Recovery (EVR) System Including In-Station Diagnostic (ISD) Systems” to “Assist Phase II Enhanced Vapor Recovery (EVR) System including In-Station Diagnostics (ISD)”; and
- Added reference to new Exhibit 13: Below-Grade Vaulted Tank Configuration.

#### Exhibit 1:

- Removed Healy Model 75 series hose assembly and figure;
- Removed Goodyear Futura HVR series hose assembly and figure;
- Added Goodyear Futura HVR Low Permeation series hose assembly and figure;
- Added Catlow Model CTMCA re-connectable breakaway and figure;
- Added VST Model VST-HEVR-SBK re-connectable breakaway and figure; and
- Removed reference to quad seals in figures 1-6 and 1-7.

#### Exhibit 2:

- Changed maximum length of hose assembly from 20 feet to 18 feet under the Inverted Coaxial Hoses section.

#### Exhibit 13:

- Added new exhibit showing typical vaulted AST configurations.

### **Part II: ARB Approved Installation, Operation, and Maintenance Manual (IOM)**

#### Table of Contents:

- Reformatted table of contents; and
- Renumbered IOM sections and combined like components into one section.

## Modification Highlights for Executive Orders VR-201-Q and VR-202-Q

### Scheduled Maintenance:

- Revised the Breakaway Reconnection section 1.4.2.

### Inverted Coaxial Hoses:

- Removed the Healy Model 75 series and Goodyear Futura HVR series coaxial hoses; and
- Added the Goodyear Futura HVR Low Perm series hoses.

### Breakaway Couplings:

- Added the Catlow Model CMTCA and VST Model VST-HEVR-SBK re-connectable breakaways.