

Modification Highlights for VR-203-K

Part I: Changes to Executive Order

Legal Language:

- Added “Whereas” paragraph describing the nature of the amendment request from Veeder Root to include the liquid condensate trap.
- Added “Whereas” paragraph requesting contractor or permit applicant to contact the local CUPA when installing or testing a liquid condensate trap.
- Added reference to new Exhibit 16: Liquid Condensate Trap Compliance Test Procedure.

Exhibit 1:

- Added rebuilt VST model “EVR SBK Rebuilt” breakaway to equipment list and figures.
- Added alternate curb and whip hose ferrule sleeve identification.
- Added a new liquid condensate trap equipment list and associated figures.

Exhibit 2:

- Added another specification to the Hirt VCS 100 Thermal Oxidizer stating that processor shall be installed at least 20 feet from the P/V vent valves.
- Added a third Clean Air Separator specification stating that ball valves shall be locked in open position during normal operation.
- Removed reference to GDF-09 for nozzle interlock equipment defect. Added new language for nozzle interlock equipment defect, e.g. live lever with nozzle bellows or sleeve uncompressed.
- Added new section related to liquid condensate traps.

Exhibit 4:

- Added Clean Air Separator in first paragraph of exhibit.

Exhibit 16

- Added new Liquid Condensate Trap Compliance Test Procedure. Added the flexibility of introducing gasoline in the LCT at either the LCT Fuel Entry Point or dispenser riser.

Exhibits 1-16

- Updated headers and footers to reflect Revision K

Part II: Changes to ARB Approved Installation, Operation, and Maintenance Manual (IOM)

Table of Contents

- Added new Section 20: Liquid Condensate Trap Installation, Operation, and Maintenance Manual

Section 20:

- Added Section 20: Liquid Condensate Trap Installation, Operation, and Maintenance Manual

Sections 1-20

- Where applicable, updated headers and footers to reflect Revision K